

# **PRODUCT FEATURES**

- · For use on any push, pull or swingthrough door
- Activates electronic release via DPST 2A rated relay when touched to allow free egress
- · Backup push button
- 16 ft. [4.8m] 22AWG 6 conductor cable and armored door cord included
- Automatic dual-voltage 12 VDC/24
- MagnaCare® lifetime replacement, no fault warranty

# **PRODUCT OPTIONS**

• (EL) ElectroLynx® ready

# **SPECIFICATIONS**

- · ANSI/UL 294 Listed
- CSA-C22.2 No.205 Listed
- CSFM California State Fire Marshal Approved
- · MEA- City of New York Approved
- CE: EN 50091-1, EN 61000-6-2 Approved

### **Dimensions:**

5"L x 2-1/8"D x 9"H

#### **Electrical:**

40 mA at rest; 25 mA releasing at 12 VDC or 24 VDC

# **Operating Temperature:**

+32 to +110F [0 to +43C] Indoor use only

# **Shipping Weight:**

3 lbs [1.36kg]

# Finishes:

BK - Black anodized

CL - Clear anodized


# **TSH**

# Touch Sense® Handle

# **Compact Push or Pull Egress Alternative for** Maglock Release

Sized to conceal existing mounting holes, the TSH Touch Sense Handle replaces standard pulls on aluminum doors to allow maglock release for egress. With flexible options, it works equally well on in-swing doors or as a push-open device for out-swing doors, offering a clean look on aluminum frame glass doors.

>> MODELS		PART #   Description
TSH-BK	TSH - Push/Pull, Black Anodized	
TSH-CL	TSH - Push/Pull, Clear Anodized	
EL-TSH-BK	TSH - Push/Pull, Black Anodized, ElectroLynx®	
EL-TSH-CL	TSH - Push/Pull, Clear Anodized, ElectroLynx®	











ASSA ABLOY, the global leader in door opening solutions

