

62



#### **PRODUCT FEATURES**

- Activates a DPDT 2 Amp rated output when pushed or pulled, to allow free egress or initiate an exit delay timer
- 16 ft. [4.8m] 22AWG 3 conductor cable and armored door cord
- MagnaCare Lifetime Replacement No Fault Warranty

#### **PRODUCT OPTIONS**

· Available ElectroLynx® ready

#### **Dimensions:**

5"L x 2-1/8"D x 9"H


### **Shipping Weight:**

1.5lbs [0.68kg]

#### Finishes:

BK - Black anodized

CL - Clear anodized



EMH Movement

**SECURITRON**.COM

# **EMH**

# **Electromechanical Handle**

## **Mechanical Motion for Mag Release in a Compact Handle**

The EMH ElectroMechanical Handle works on any push, pull or swing-through door, and is designed for specialized outdoor applications. Pressing the Handle activates internal mechanical switches that release the lock. Meets "no special tools or knowledge" criteria for code requirements.

>> MODELS		PART #   Description
EMH-BK	Touch Handle - Electromechanical, Black Anodized	
EMH-CL	Touch Handle - Electromechanical, Clear Anodized	
EL-EMH-BK	EMH - Black Anodized, ElectroLynx	
EL-EMH-CL	EMT - Clear, ElectroLynx	

