

OUTDOOR EMERGENCY PHONES

ETP-401C – Single Button Information Phone

Description

Model **ETP-401C** is an outdoor-rated, ADA-compliant hands-free Emergency Phone for use in locations such as: parking facilities, college campuses, controlled access gates, medical centers and industrial parks.

Features

- · Cast metal raised letter and Braille signage for ADA compliance
- · Vandal resistant stainless steel faceplate and metal button
- Uses regular phone lines or PBX
- · Phone line powered: no power supply or battery back-up needed
- Circuit boards are conformally coated for water protection
- · LED indicator for hearing impaired
- Auxiliary input and outputs to integrate with CCTV, Blue Light Strobe, Scream Alert[™] and other devices
- Built-in auto-dialer can dial two numbers: if first number doesn't answer or is busy, dials second number.
- · Auto-answer allows security to monitor and initiate calls with Emergency Phone
- Options available that offer the ability to automatically identify attendant of location of calling phone by recorded message and digital display

Specifications

Construction:	12 gauge (2.8mm) #4 brushed stainless steel faceplate
Dimensions:	6.81(173) W x 9.94(252) H x 2.88(73) D in(mm)
Weight:	8 lbs. (3.6kg)
Operating Temperature:	-4ºF to +149ºF (-20ºC to +65ºC)
Mounting:	Surface mounts with rear wire entry
Communication:	2-way hands-free communication
Digit Capacity:	Up to 18 digits, including pauses, for each of two phone numbers
Dialing Speed:	Approximately 10 tones per second
Power Source:	Phone line powered (requires 20mA at 24 v off-hook)
Connection:	Parallel tip and ring connected to RJ11 connector for quick installation
Circuit Protection:	Varistor lightening suppressed and full wave polarity guarded
Programming:	Non-volatile EEPROM programming can be done from any telephone.
"On Time":	Programmable from 1-4270 minutes in 1-minute increments.
Wiring Requirements:	1 twisted-shielded pair
Compliance:	CSA Certified to UL Standard 60950
	0 00


Options & Accessories

Voice Location Identifier:	Model ETP-401CV includes the capability to record a message identifying the location of the call. Message is recorded and duration set during programming.
Faceplate Camera:	Add "OP3" to model number to add a color pinhole camera mounted discreetly behind the faceplate. Add "OP3BW" for a b/w camera.
"EMERGENCY" Casting:	Use Model ETP-401 for a button that reads EMERGENCY instead of TO CALL
Mounting Extension:	Use Model ETP-SME to allow easy conduit entry
8-Line Consolidator:	Model EC-8 allows connection of up to 8 phones on one phone line while retaining ability to call each phone individually. Can also create a closed system without need for any phone lines.
Monitoring/Diagnostic Software Package:	Talk-A-Lert®, model ETP-TAL, automatically polls each Emergency Phone, reports incoming calls and keeps permanent records of all events



ETP-401C – Single Button Outdoor Information Phone

Dimensions



Copyright 2009 Talk-A-Phone Co. All rights reserved.