



**SILENT
KNIGHT**

by Honeywell

B200SR

Intelligent Sounder Base

The B200SR sounder base sets a new standard for performance, installation ease, and aesthetics. It offers maximum flexibility in installation, configuration, and operation to meet or exceed UL 268 and UL 464 requirements.

For more information about the IntelliKnight system, or to locate your nearest source, please call 1-800-328-0103.

Description

B200SR

The B200SR Series sounder bases set a new standard for performance, installation, and aesthetics. The B200SR is designed for new and existing dwelling unit applications. It offers maximum flexibility in installation, configuration, and operation to meet or exceed UL 268 and UL 464 requirements.

The B200SR is fully compatible with existing B501BH-Series sounder base installations. The device enables users to select one of two B501-supported tones (ANSI Temporal 3 or Continuous) by removing a jumper.

With its attractive aesthetics, the B200SR is ideal for applications where appearance is critical. For example, the sounder base employs a separate mounting plate that installs on various junction box sizes to eliminate unsightly surface-mount boxes. In addition, the mounting plate enables pre-wiring of all connections to speed and simplify installation. The housing then mates with the mounting plate and is locked in position with two retaining screws, which are covered by the installed sensor head for added tamper resistance.

Features:

- Tone selection via an onboard jumper
- UL 268 and UL 464 compliant
- Pre-wire mounting plate fits various junction box sizes
- Fully compatible with existing B501BH-Series sounder base installations
- Mechanical locking feature prevents the removal of the attached sensor head

Installation

The B200SR can be mounted directly into a 4" square by at least 1.5" – 2.1" deep electrical box, using the supplied mounting kit.



B200SR

Compatibility

The B200SR is compatible with the following SK-series detectors:


- SK-Photo Photoelectric Smoke Detector and SK--Photo-T Photoelectric Smoke Detector with Thermal
- SK-Acclimate Multicriteria Photoelectric Smoke Detector
- SK-Ion Ionization Smoke Detector
- SK-Heat Fixed Temperature Thermal Detector, SK -Heat-ROR Rate-of-Rise Detector with Thermal, and SK-Heat-HT Fixed High Temperature Thermal Detector

The B200SR is compatible with the following IntelliKnight FACP's:

5700
5808
5820XL
5820XL-EVS

Model B200SR

Intelligent Sounder Base



Specifications

Physical

Height:	2.0" (5.08 cm) less sensor
Width:	6.875" (17.46 cm)
Shipping Weight:	0.50 lb. (227 gm)

Electrical

External Supply Voltage	16 to 33 VDC (VFWR)
External Supply Standby Current	500 μ A maximum
Alarm Current	35 mA maximum
SLC Operating Voltage	15 to 32 VDC
SLC Standby Current	300 μ A maximum

Environmental

Operating Temperature:	32°F – 120°F (0°C – 49°C)
Humidity:	10% – 93% non-condensing

Sound Output

Greater than 85 dBA minimum measured in a UL reverberant room at 10 feet, 24 Volts (in continuous tone)

Ordering Information

B200SR Intelligent Sounder Base



**SILENT
KNIGHT**

by Honeywell

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice. For more information, contact Silent Knight 12 Clintonville Road, Northford, CT 06472-1610 Phone: (800) 328-0103, Fax: (203) 484-7118. For Technical Support, Please Call 800-446-6444.
www.silentknight.com

MADE IN AMERICA

FORM# 350267 Rev B
© 2013 Honeywell International Inc.