

Series FLS Audible Strobe



The Series FLS Audible Strobe combines a high output audible alarm with a strobe that makes it the perfect choice for many applications including security and process alarms.

High sound output with volume control
 24VDC
 Automatic synchronization
 Choice of lens and alarm color combinations
 Base compatible with the Series ROS and CLR
 Indoor

Nominal Voltage: 18 - 30VDC
 Current Consumption (tone dependant): 68mA (average)
 Sound Output (tone dependant): 101dB
 Alarm Tones: 2
 IP Rating: IP54 w/ deep base, *IP65 w/ shallow base (ordered separately)
 Color: Off White
 Flash Rate: 1 Hz (60 per min)
 Strobe Type: U-Tube
 Operating Temperature: -10°C to 55°C
 Monitoring Mode: Polarized Diode
 Volume Control: 0 to -20dB

Specification and Ordering Information:

Model Number	Order Code	Description
FLS-R-DC	4068	Red Lens
FLS-A-DC	4069	Amber Lens
FLS-B-DC	4070	Blue Lens
DB	4090	Deep Base



WE ENCOURAGE AND SUPPORT NICET CERTIFICATION
 3 YEAR WARRANTY

FLS 02/08



NJ Location
 273 Branchport Ave.
 Long Branch, NJ 07740
 P: 800-631-2148
 F: 732-222-8707
www.coopernotification.com

FL Location
 7565 Commerce Ct.
 Sarasota, FL 34243
 P: 941-487-2300
 F: 941-487-2389

VA Location
 P: 877-459-7726
 F: 703-294-6560