

## GSM Antennas

GSM-ANT



GSM-ANT3dB



Honeywell offers remote antennas designed to increase GSM signal transmission capability. These durable, low-profile antennas are designed to allow flexible integration with GSM communication devices.

The GSM-ANT Indoor Fixed Length Antenna is designed for indoor use. It comes with 10ft. of RG-174 cable and mounting hardware for ease of installation.

The GSM-ANT3dB Weatherproof Remote Antenna optimizes transmissions with field diversity technology. The versatile, weatherproof design is suitable for indoor or outdoor applications.

## SPECIFICATIONS

### Electrical

#### GSM-ANT

- Frequency Range:
  - 824-896 MHz
  - 1850-1990 MHz
- Average Gain: 1dBi
- Maximum power: 10W
- Nominal impedance: 50 ohms
- Pattern: Omni Directional
- Termination: SMA Male

\* For Indoor Use Only

#### GSM-ANT3dB

- Frequency Range:
  - 821-896 MHz
  - 1850-1990 MHz
- Average Gain: 3dBi
- Maximum power: 100W
- Nominal impedance: 50 ohms
- Pattern: Omni Directional
- Termination: N Female
- Operating Temperature: -40° to 185° F (-40° C to 85° C)

\* Fully Weatherproof for Outdoor Application

## ORDERING

#### GSM-ANT

Fixed Length Antenna

#### GSM-ANT3DB

Weatherproof Remote Antenna

#### GSM3DBKT

Includes **GSM-ANT3DB** antenna and **WA7626-CA SMA** to N adaptor cable

#### GSM3DB25KT

Includes **GSM-ANT3DB** antenna, **WA7626-CA SMA** to N adaptor cable, 25 ft coax cable

#### GSM3DB50KT

Includes **GSM-ANT3DB** antenna, **WA7626-CA SMA** to N adaptor cable, 50 ft.coax cable

### Honeywell Security & Custom Electronics

Honeywell  
2 Corporate Center Drive  
Melville, NY 11747  
Tel: 800.467.5875  
www.honeywell.com