CAIPHONE Parts Reference Guide for **GT Series Multi-Tenant Entry Security Intercom**

Easy to customize – mix and match any combination of stations!

Install up to 16 entrance stations, 4 concierge/guard stations, and 500 tenant stations or telephone line adaptors.

Tenant Station Comparison							
Features ► Tenant Stations ▼	7" LCD Screen (wide display)	Door Release (unlocks entrance)	Hands-Free Communication (VOX or PTT)	PTZ Control (170° in wide view)	Picture Memory (records visitors)	Personal Tenant Door Station (replaces the peephole)	Internal Communication (4 stations per apartment)
GT-2C		√	✓	✓	✓	√	√ (1 GT-2C + 3 GT-2Hs)
GT-1C7	✓	✓	✓	✓			
GT-1M3		✓	✓	√ (zoom only)			
GT-1A		√	✓				
GT-1D		√					

Tenant Stations & Telephone Line Adaptor (mix and match up to 500)

Full-Featured** Tenant Master & Sub Master Stations



GT-2C

Video Tenant Master Station

- · Video identification and monitoring with 3-1/2" LCD screen
- Hands-free communication
- Compatible with personal tenant door stations

GT-2C requires

power supply.

a separate



Video Tenant Sub Master Station (requires GT-2C)

- Video identification and monitoring with 3-1/2" LCD screen
- Hands-free communication
- Up to 3 per GT-2C

Only the full-featured tenant stations

support internal communication with 1 GT-2C + 3 GT-2Hs per tenant.

Tenant Stations*



GT-1C7

Video Tenant Station Video identification and monitoring with

- 7" LCD screen Hands-free communication
- Sleek, slim design



GT-1M3

Video Tenant Station

- · Video identification and monitoring with 3-1/2" LCD screen
- Hands-free communication
- Sleek, slim design



GT-1A **Audio Tenant** Station

 Hands-free communication



GT-1D **Audio Tenant** Station

 Handset for privacy

Telephone Line Adaptor



Telephone Line Adaptor (required per tenant)

 Provides ability for a single resident to answer calls and unlock doors using a telephone



Security Guard/ Concierge Station (up to 4)



Security Guard / Concierge Station nown with optional GFW-S desk stand)



GT-MK requires a separate

Personal Tenant Door Stations (1 per GT-2C)



GT-D

Audio Door Station

- Plastic chassis
- Surface mount



*Up to 4 stations per tenant with these

JK-DA

Video Door Station

- Plastic chassis
- PTZ camera Surface mount



parameters: 1 GT-1C7 + 3 audio stations OR 2 GT-1M3s + 2 audio stations OR 4 audio stations.

JK-DV

Video Door Station

- · Zinc die cast cover
- PTZ camera
- Surface mount



JK-DVF

Video Door Station

- Stainless steel panel
- PTZ camera
- Flush mount (back box included)



JK-DA, JK-DV, and JK-DVF have a wide angle camera, allowing users to view up to 170° of the entry area.

Power Supply, Control Units, and Accessories



PS-2420UL 24V DC, 2A **Power Supply**



GT-BC Audio **Control Unit**



GT-VBC Video **Control Unit**



GT-4Z 4-Way Video Distribution Adaptor



GTW-VOA Video Output Adaptor



GT-BCX Expanded

Audio Control Unit (includes mounting rail)





GT-VBX Expanded Video Control Unit (includes mounting rail)



GTW-LC Multi-Relay Control Unit (includes mounting rail)





or GT-2H



W-DIN11

DIN Mounting Rail for GT-BC, GT-VBC, GT-4Z, or GTW-VOA



GT-RY External Signalling Relay



Mix and match up to 16 All-In-One Entrance Stations, Modular Entrance Station Kits, or Custom Entrance Stations

All-In-One Entrance Station

Ready-to-Install Single Panel with Digital Scroll Buttons

Modular Entrance Station Kits

Ready-to-Assemble Modular Kits with Digital Scroll Buttons





Modular Components for Custom Entrance Stations





Mix and Match with Required Audio Panel/Module - Compatible with Direct Select and Digital Scroll Options



Mounting Components for Entrance Stations

Need assistance specifying the GT Series? Use the online QuikSpec tool. Register

for free, save in multiple formats, and download the specs! aiphone.com/quikspec

