



HHDO15D1G 2.8 - 10mm auto iris varifocal lens, dark grey housing

Features

- 1/3" Panasonic CMOS image sensor
- 2.1M pixels Full-HD video resolution
- Supports 1080p @ 30fps & 720p @ 60fps
- Simultaneous analog composite video output for easy service & camera installation
- Chameleon Cover™: Snap-on cover converts the housing from standard dark grey to decorator white and can be painted to match any décor*
- 3-axis wall and ceiling mount
- Full OSD operation
- 12VDC / 24VAC dual voltage operation
- Vandal resistant operation
- Weather resistant operation
- IP66 compliant
- 5 year warranty



Specifications

Image Sensor	1/3" Panasonic 2.1M pixels CMOS sensor	BLC / HSBLC	Off / BLC / HSBLC
Resolution.....	1920 x 1080p	ACE	High / Middle / Low / Off / On
Minimum Illumination.....	0.5 lux @ F1.2, 0.01 lux (sense-up x60)	Sharpness	1-100 level adjustable
Effective Pixels	1944 (H) x 1092 (V), 2.12M pixels	D-Zoom.....	x64 (PIP)
Scanning System.....	Progressive	Motion Detection.....	3 zone
S/N Ratio	More than 50dB (AGC off)	Privacy.....	8 zone
Shutter Speed.....	Auto, 1/25 sec. – 1/50,000 sec., x2-x30	Video Output.....	HD-SDI, CVBS simultaneously
Sense-Up.....	Off / Auto x2-x30	Power Supply	12VDC / 24VAC dual voltage operation (power supply not included)
Day & Night	Color / BW / Auto / EXT	Power Consumption	12VDC, 250mA / 24VAC, 120mA
Lens Type	DC / Manual	Operating Temperature.....	-4° F – 140° F
AGC.....	High / Middle / Low / Off	Dimensions.....	3.46" (H) x 5.1" (Dia.)
White Balance	ATW / AWC - SET / Indoor / Outdoor / Manual	Weight	1 lb.
DNR.....	High / Middle / Low / Off		

Optional Accessories



* Chameleon Cover™ is for indoor use only. It must be painted with waterproof paint if used outdoors.

Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 1/18/13

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880
www.specotech.com