

Intensifier H® Series Miniature Weather/Vandal/Tamper Resistant Dome Camera with Chameleon Cover™

See Color In Almost Complete Darkness Without IR LEDs


HINT13H 3.6mm fixed lens, dark grey housing

Features

- 1/3" Sony Super HAD™ CCD
- 700 lines of color resolution
- Amplify existing light with no distance limitations
- No problems caused by objects that reflect or absorb IR light sources
- Minimum illumination 0.00002 lux (Intensify @ 512x)
- Chameleon Cover™: snaps on and can be painted to match any décor!*
- Full OSD operation
- Now with presets: Outdoor, Indoor, Elevator, Lobby, Hallway & Dark
- Wall or ceiling mount
- 12VDC / 24VAC dual voltage operation
- Vandal resistant operation: can withstand hits from a 10 lb. sledgehammer!
- Tamper resistant operation: tamperproof screws for enhanced security
- Weather resistant operation: good for indoor or outdoor usage
- IP66 compliant
- 5 year warranty



Shown with included paintable, snap-on Chameleon Cover™



Specifications

Image Sensor	1/3" Sony Super HAD™ CCD
Resolution.....	700 TV lines
Minimum Illumination.....	CDS Off: 0.15 lux CDS On: 0.00002 lux
Effective Pixels	976 (H) x 494 (V)
Total Pixels	1020 (H) x 508 (V)
Scanning Frequency.....	15.734kHz (H) & 59.94Hz (V)
Scanning System.....	2:1 interlace
Synchronization	Internal
S/N Ratio	More than 52dB
Video Output.....	CVBS: 1.0Vp-p / 75 ohms
Electronic Shutter Speed.....	1/60 sec. – 1/120,000 sec.
OSD.....	Available
DWDR	On / Off (level adjustable)
Backlight Compensation.....	BLC / HLC / Off
Day/Night.....	Color / BW / Auto
AGC.....	High / Low / Off

White Balance	ATW / Indoor / Outdoor / Manual AWC (1,700°K – 11,000°K)
Intensify	Auto / Off (selectable x2 - x512)
Motion Detection.....	On / Off (8 programmable zones)
Privacy Masking	On / Off (8 programmable zones)
Speco DNR.....	On / Off (level adjustable)
Digital Zoom	On / Off (1x - 8x)
DIS.....	On / Off
Sharpness	On / Off (level adjustable)
Flip / Mirror	On / Off
Power Supply	12VDC / 24VAC dual voltage operation (power supply not included)
Power Consumption	12VDC, 130mA / 24VAC, 75mA
Operating Temperature.....	-20° F – 122° F
Dimensions.....	3.07" (H) x 4.33" (Dia.)
Weight	1.54 lbs.

* Chameleon Cover™ - for best results when used outdoors, waterproof paint is recommended. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 1/17/14



Optional Accessories



PSW4
24VAC
Power Supply



PSW5
12VDC
Power Supply