

II - E1500-23

EXIT DEVICE INSTALLATION INSTRUCTIONS

AUTHORIZED EGRESS SWITCH (AE) AND LATCH MONITORING SWITCH (LM)

FOR USE WITH ALL ACSI MONITORED EXIT DEVICE MODIFICATIONS

AUTHORIZED EGRESS (AE) SWITCH MONITORS EGRESS BY PUSHBAR ACTIVATION OF EXIT DEVICE

LATCH MONITORING (LM) SWITCH MONITORS THE LATCH MECHANISM OF EXIT DEVICE

AUTHORIZED EGRESS (AE)

ELECTRICAL SPECIFICATIONS

- SPDT MONITOR SWITCH
- CONTACT RATING: 3 AMP @ 125VAC
2 AMP @ 30VDC

COLOR CODE FOR WIRES

- YELLOW WIRE: COMMON
- RED WIRE: NORMALLY OPEN
- GRAY WIRE: NORMALLY CLOSED
- WIRE GAUGE: #22 AWG

LATCH MONITORING (LM)

ELECTRICAL SPECIFICATIONS

- SPDT MONITOR SWITCH
- CONTACT RATING: 3 AMP @ 125VAC
2 AMP @ 30VDC

COLOR CODE FOR WIRES

- BLACK WIRE: COMMON
- WHITE WIRE: NORMALLY OPEN
- RED WIRE: NORMALLY CLOSED
- WIRE GAUGE: #22 AWG

NOTES: 1.) USE MANUFACTURER'S TEMPLATING FOR
DOOR PREPARATION. PROVIDE ADDITIONAL PREP
AS SHOWN ON ACSI EXIT DEVICE TEMPLATE E1500-XX
(CONSULT FACTORY FOR PROPER TEMPLATE)

