

## INSTALLATION INSTRUCTIONS K-130 AUTHORIZED EGRESS (AE) SWITCH KIT

FOR USE WITH JACKSON 20 SERIES EXIT DEVICES

**Electrical Specifications:**

Wire Leads: 22AWG  
SPDT Monitor Switch:  
Contact Rating: 3A @ 125VAC  
2A @ 30VDC

**Wire Color Codes:**

Yellow Wire: Common  
Red Wire: Normally Open  
Gray Wire: Normally Closed

**Installation:**

1. Separate the touch bar cover from the touch bar assembly.
2. Separate the touch bar assembly from the mechanism housing at the front and rear mechanism housing mounts.
3. Remove the rear touch bar mount from the touch bar assembly.
4. Locate the K-130 Kit between the rear touch bar mount and the touch bar assembly.
5. Attach the rear touch bar mount to the touch bar assembly. Verify the switch bracket is not prohibiting the rear touch bar mount from being secured flush to the touch bar assembly.
6. Route the lead wires along the side opposite of the dogging assembly location.
7. Secure the lead wires to the inside of the touch bar assembly using the supplied ty-wrap mount and ty-wrap.
8. Attach the touch bar assembly to the mechanism housing at the front and rear mechanism housing mounts.
9. Attach the touch bar cover to the touch bar assembly.
10. Drill a 1/4" diameter hole through the end cap for wire access from the access control system to the exit device.

SWITCH MONITORS TOUCH BAR DEPRESSION

RIGHT HAND REVERSE DEVICE SHOWN

