



IR151B, IR152B Patient Stations

IL727 Specification Sheet

Tek-CARE® NC150 & NC200 Nurse Call Systems • Rev. 5 - 04/2013

Features

- UL® 1069 Listed
- May be used as a retrofit for the IR151N or IR152N station with IH106N backbox; requires two CL207 mounting adapters.
- Push button calling
- Call-placed indicator
- In-use indicator when intercom audio path is active
- Reset button
- Sensitive speaker/microphone
- Attractive and durable flame-retardant (UL® 94V-0) plastic panel

Description

The IR151B or IR152B Patient Station provides for efficient use of the nursing staff by permitting fast and reliable communication between staff and patient. Calling the nurse is accomplished by pressing the call button on the end of a 6' or 10' long call cord. A non-resettable call is registered if the call cord is accidentally removed from its jack.

Call-placed assurance and intercom operation are indicated by solid-state LEDs. The speaker/microphone is sensitive enough to assure clear conversation, even with weak patients. A reset button is provided on the durable, flame-retardant (UL® 94V-0) plastic panel.

Listings



UL® 1069 listed; UL® File Number E71599.



**IR151B
Single Patient
Station**

**IR152B
Dual Patient
Station**



IR151B, IR152B Patient Stations

Specifications

Dimensions:	Height:	4.5"	(119 mm)
	Width:	6.375"	(162 mm)
	Depth:	1.875"	(48 mm)
	Projects:	0.5"	(12.7 mm)
			above mounting surface
Speaker:		2.5" x 2.5"	
Connections:		Plug-in type	
Housing:		Steel City #H3BD with Steel City #3GC plaster ring, or if a smaller box is needed, use ARC-CO #3GB with ARC-CO #3GC ring.	
		Horizontal mount.	

Required Components

Tek-CARE®NC200 or NC150 Nurse Call System
SF301 or SF301/10 Call Cord

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3
TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)