

### MANUAL INTERCOM SYSTEMS

## **KB-LC-2W – Single Channel Master**

## **Description**

The **KB-LC-2W** is a durable, reliable solution for any single-channel application where the Master does not need to talk hands-free

#### **Features**

- · Master presses one button to talk
- Sub-station speaks hands-free
- Incoming call announced by tone
- Stand-by mode allows Master to silence sounds from sub-station
- Completely self-contained—no separate junction box or amplifier
- Connect multiple speakers in parallel



Construction: Vinyl coated Steel

Dimensions: 10.50(267) W x 3.13(80) H x 8.75(222) D in(mm)

Weight: 7 lbs. (3.2kg)

Mounting: Designed for desk mounting

Power: 120VAC required for 24VDC, 600mA power supply

Cable: 1 shielded pair needed for all sub-stations

## **Options & Accessories**

Paging Booster: Model **K-HP-50** provides 50 watts of power

**Sub-Stations** 

With Call Button: Model K-LR-3W flush mounts—use K-SM-L accessory to surface mount. Model K-LR-3

is a desk-style version of K-LR-3W.

Without Call Button: Model K-LR-2R flush mounts—use K-SM accessory to surface mount. Model K-LR-2 is a

desk-style version of K-LR-2R.

Cradle Phone: Model K-S-112X provides clear communication and privacy in a noisy environment. Use

with model K-C-20 horn speaker so master can call person at cradle phone location. Horn

disconnects when cradle phone is picked up.

Horn Speaker: Model K-C-20 furnishes up to 4 times the volume of sub-station K-LR-2R. Model K-C-20V

includes built-in volume control.

High-Powered: Model **K-HP-3** is a 5 watt speaker for indoor use. Model **K-HP-3V** includes built-in volume

control.

Ceiling Speaker: Model **S-8318B** is an 8" ceiling speaker with white metal baffle and built-in volume control.

For indoor use.

Gas Dispenser: Model **\$-8304** is a built-in speaker for gas dispensers. No call origination or volume

control.



Rev. 10/25/10

# **KB-LC-2W – Single Channel Master**

## **Dimensions**



