

LYNX Plus WIRELESS CONTROL PANEL



With its uncompromising technology, reliability and self-contained architecture, Honeywell's LYNX Plus is an easy-to-install security system. LYNX Plus is a combination control panel, keypad, siren, dialer, two-way voice system and speakerphone in one. It offers full Contact ID information to your central station via TELCO, Internet GSM communications using the GSMVLP. It also offers two-way voice over GSM radio using the GSMVLP. Whether used as backup or primary, 4G radio finds the best alarm signal in the area—improving longevity, enhancing speed and maximizing installation opportunities.

The new communications options give you the flexibility you need to address the emergence of VoIP, POTS migration to cellular and the growth of digital radio networks.

The convenient voice prompt programming feature walks you through the installation process—helping reduce installation costs. Voice annunciation of system status and alarm conditions greatly reduce the amount of end-user training. LYNX Plus supports all Honeywell 5800 Series wireless devices, including the 5828 and 5828V wireless keypads.

FEATURES

Dealer

- Supports two-way voice over GSM radio (with the GSMVLP radio module)
- Supports Honeywell Total Connect™ Remote Services
- Advanced Protection Logic – With APL enabled, the alarm can be reported even if the system is damaged during the entry and communications delay times. APL can be selected when using Honeywell GSM and IP communicators.
- GSM signal strength indicator on the display
- Up to 40 wireless zones
- One hardwired zone onboard
- Voice prompt programming mode
- Lack of usage notification
- Real time clock

- Full 16-button keypad with easy-to-read LCD display and status LEDs
- Built-in two-way voice system
- Hinged front and back cover for simpler installations
- Wall or optional desk-top mounting
- 85 dB internal sounder with voice siren
- Internal speaker and microphone
- Eight user codes
- 84 event log
- Fully downloadable
- Rechargeable battery backup
- Scheduling

End-user

- 2 x 16 Custom Alpha backlit display
- "Follow Me" alarm and reminder announcements

- Voice prompted clock setting
- Full voice response
- Family message center that records and plays back voice messages
- Speakerphone operation
- Remote phone control
- Optional bidirectional remote provides system status feedback
- Optional wireless, programmable remotes offer single-button system control
- Activates lights, appliances, garage doors and numerous other applications with the touch of a button or at specified times
- Quick exit feature enables users to leave the house for a brief time without disarming the system
- Chime by zone feature sounds chime and speaks location in plain English
- Single button operation

LYNX Plus

WIRELESS CONTROL PANEL

SPECIFICATIONS

General Specifications

- Full Contact ID reporting
- Up to 40 wireless zones
- 2 x 16 Custom Alpha backlit display
- Family message center with voice recording and playback
- Single-button operation
- Multiple default settings for easy programming
- Full voice response
- Remote downloading
- Eight user codes
- 84 event log
- Chime by zone
- Quick exit
- Real-time clock
- Scheduling
- Operating temperature: 32°F - 122°F (0° C - 50°C)
- Rechargeable battery backup
- RF enrollment speeds installation of wireless keys and transmitters

Physical Dimensions

- 8.8" W x 6.8" H x 1.9" D

Electrical

- Voltage Input: 9VAC from plug-in 25VA transformer
- Rechargeable Backup Battery:
 - Six 1.2V/cell nickel-metal hydride rated at 1100 mA
 - Optional 6V 3.1Ah delivering up to 24 hours of standby operation
- Alarm Sounder:
 - Bell = 6-14VDC, 120mA max (e.g., WAVE2EX)

Integrated Wireless Receiver

- LYNX Plus receiver supports
 - Up to 40 wireless zones
 - Two-way wireless devices with status feedback: 5804BD, 5804BDV, 5828, 5828V and 5827BD
 - Diversity reception with two antennas
 - Indications by zone and low battery indicator

Communications

- Formats supported:
 - ADEMCO Express: 10 characters/sec, DTMF (TouchTone) Data Tones, 1400/2300 Hz ACK, 1400 Hz KISSOFF
 - ADEMCO Contact ID Reporting: 10 characters/sec., DTMF (TouchTone) Data Tones, 1400/2300 Hz ACK, 1400 Hz KISSOFF
 - ADEMCO Low Speed: 10 pulses/sec, 1900 Hz Data Tone, 400 Hz ACK/KISSOFF
 - Radionics/SESCO: 20 pulses/sec, 1800 Hz Data Tone, 2300 Hz ACK/KISSOFF Can report 0-9, B-F.
- Line Seize: Double Pole
- Ringer Equivalence: 0.6B
- FCC Registration No.: 5GBUSA-25623-AL-E

ORDERING

U.S.

L3000

L3000PK

L3000-SIA

L3000LB

L3000LBSIA

L3000-SP

L3000DM

GSMVLP4G

GSMVLP-KT

LYNXRCHKITSH

LYNXRCHKITHC

LYNXRCHKITSC

K10145WH

K10145WHGN

LYNX Plus Wireless Self-Contained Security Control

LYNX Plus Wireless Self-Contained Security System (Includes three (3) 5816 Transmitters, one (1) 5890PI Wireless Motion Detector and one (1) 5804 Wireless Key Remote)

LYNX Plus Wireless Self-Contained Security Control with SIA CP-01 compliance

LYNX Plus Wireless Self-Contained Security Control, less battery

LYNX Plus Wireless Self-Contained Security Control with SIA CP-01 compliance, less battery

Spanish Language LYNX Plus Wireless Self-Contained Security Control

Desk Mount for LYNX Plus

Internal GSM Module with Two-way Voice Transport Capability

GSM Radio Kit with GSMVLP and Two-way Voice Audio Cable

24 Hr. Battery Backup for L3000 with GSMVLP4G installed

24 Hr. Battery Backup for L3000 only

4 Hr. Battery Backup for L3000 with or without GSMVLP4G installed

Transformer, White LYNX Plus (two-prong)

Transformer, White LYNX Plus (three-prong with ground)

Canada

L3000-CN

L3000CNLB

L3000-FR

L3000FRLB

GSMVLP4G

K10145CN

LYNX Plus Wireless Self-Contained Security Control

LYNX Plus Wireless Self-Contained Security Control, less battery

French Language LYNX Plus Wireless Self-Contained Security Control

French Language LYNX Plus Wireless Self-Contained Security Control, less battery

Internal GSM Module with Two-way Voice Transport Capability

Canadian Transformer, White

For more information:

www.honeywell.com/security

Automation and Control Solutions

Honeywell Security Products Americas

2 Corporate Center Dr. Suite 100

P.O. Box 9040

Melville, NY 11747

1.800.467.5875

www.honeywell.com

L/LYNXPLSD/D

November 2013

© 2013 Honeywell International Inc.