


## LCDHG SERIES 15", 17" & 19" LCD Monitors w/HDMI Inputs



SECURITY RATED | 4:3 ASPECT RATIO | 3DNR | 3D DE-INTERLACE | LOOPING BNC INPUTS

The LCDHG Series of professional, security rated LCD's are built specifically for video security applications. Designed using only A-Grade panels; the color, quality and sharpness of these monitors is outstanding. The Series offers 15" 17" and 19" models to fit your exact installation requirements. All models include HDMI inputs designed to work with the latest generation of DVR's in addition to VGA and dual looping BNC inputs. All models have removable stands for wall mounting and meet VESA 75 or 100 mounting standards. All monitors include an intuitive easy to use OSD menus making setup quick and simple. The ARM LCDHG Series is feature-packed with:

- HDMI & VGA Video Inputs
- HDMI & VGA Cables Included
- 3DNR (Digital Noise Reduction)
- 3D De-Interlace Technology
- Dual Looping BNC Inputs
- Super Fast 5ms Response Time
- PC & RCA Audio Inputs
- OSD Control
- VESA Compliant



## High Performance Security Display Devices






LCD1520HG



LCD1720HG



LCD1920HG

## HIGH PERFORMANCE

### HDMI Input

HDMI inputs allow for transmission of uncompressed video signals producing some of the highest resolution video and pictures available today.

### Up to 800:1 Contrast Ratio

Keep similar colors from blending together generating realistic color representation.

### Up to 300 cd/m<sup>2</sup> Brightness

High brightness settings help to prevent "wash out", and make it easier to see details when monitors are placed in brightly lit areas.

### Up to 1280 x 1024 Resolution

The higher your resolution the more pixels you have to work with creating images with much more detail.

### Looping BNC Inputs

Use looping BNC inputs for sending the same video to multiple monitors.

## CONVENIENCE

### Multiple Video Inputs

Choose the input that works the best for your application, available inputs include high resolution HDMI, VGA and BNC.

### Multiple Monitor Sizes

Choose from 15", 17" and 19" sizes to easily fit the installation space available for display devices.

### Space Saving Design

An LCD's flat-panel, space-saving design is more professional looking and functional either desk or wall mounted.

### Easy To Use OSD

All models offer easy to use On Screen Displays which allow users to fine tune their display settings including brightness, contrast, color, even language settings.

## TOTAL SECURITY

### High Quality Panels

All monitors are built using only A-Grade LCD panels. A-Grade panels will last longer, have fewer "dead pixels" and resist burn-in and etching.

### Composite BNC Inputs

Most DVR's are equipped with single BNC and VGA monitor outputs. For installations requiring multiple display devices; a monitor with both BNC and VGA inputs saves time and money by eliminating the need for splitters and other peripheral devices.


### Built-In Audio

All models include built-in speakers with PC and RCA input options giving you the ability to look and listen; perfect for facilities requiring constant monitoring where audio and video surveillance is essential.

# LCDHG SERIES 15", 17" & 19" LCD Monitors w/HDMI Inputs

REAR PANEL DEFINITIONS | TECHNICAL SPECIFICATIONS | ACCESSORIES

## REAR PANEL DEFINITIONS



## SPECIFICATIONS

	SPECIFICATIONS	LCD1520HG	LCD1720HG	LCD1920HG
GENERAL	Native Resolution	1024 x 768 @ XGA	1280 x 1024 SXGA	
	Active Display Area	11.96" x 8.97"	13.38" x 10.7"	14.88" x 11.96"
	Supported Resolution		640 x 480 VGA 800 x 600 SVGA 1024 x 768 XGA	
		N/A	1280 x 1024 SXGA	
	Impedance		75 Ohms	
	Video Input Signal		1V (p-p)	
	Aspect Ratio		4:3	
	Pixel Pitch	0.297 x 0.297 (mm)	0.264 x 0.264 (mm)	0.294 x 0.294 (mm)
	Color Depth		16.7M	
	Brightness	260 cd/m2	300 cd/m2	
	Contrast Ratio	700:1	800:1	
	Viewing Angle (H/V)		160° / 160°	
	Response Time	8ms	5ms	
	Lamp Life Time (Min.)		> 25,000 Hours	
	Auto Adjustment		Yes	
Certificates		Energy Star, UL/CUL, FCC-DOC, CE, ROHS		
ELECTRICAL	Input Voltage	AC 100 ~ 240V		
	Power Supply	12 Volts DC		
	Power Consumption	35 Watts		
OSD	BNC	Picture Mode - Contrast, Brightness, Color, Tint, Sharpness, Color, DNR   Sound Mode - Volume   Setup Mode - Language, Source   Video Settings - H.Position, V.Position		
	VGA / HDMI	Picture Mode - Contrast, Brightness, Color   Sound Mode - Volume   Setup Mode - Language, Source   Video Settings - H.Position, V.Position		
CONNECTIONS	Video	BNC In/Out (x2) VGA (x1) / HDMI (x1)		
	Audio	RCA (x2 - Stereo) PC Audio In (x1)		
PHYSICAL	Dimensions (Monitor only)	12.25" x 14.4" x 1.9" (HxWxD)	14.6" x 16.5" x 2.4" (HxWxD)	14.6" x 16.9" x 2.5" (HxWxD)
	Weight	6.6lb	12.8lb	13.2lb
	Package Weight	8.6lb	13.3lb	14.4lb
	Package Dimensions	17.0" x 19.5" x 5.0"	19.6" x 22.0" x 6.12"	19.6" x 22.0" x 6.12"
	Operating Temp		23° ~ 104°F	
	Storage Temp		-13° ~ 140°F	

## INCLUDED ACCESSORIES



## RECOMMENDED ACCESSORIES

