



LI381 Corridor Light - LI382 Corridor Zone Light



Architects' And Engineers' Specifications

The corridor dome lights shall be Alpha Communications® / TekTone **LI381**, and the corridor zone lights shall be Alpha Communications® / TekTone **LI382**, or approved equal. Lights shall include a translucent plastic cover mounted on a flame retardant ABS plastic panel, which shall be removable for bulb replacement, without the use of any tools. The **LI381** and **LI382** shall be U.L. 1069 listed, to the latest standards. Units shall mount over a conventional 2-gang electrical back box.

Contractor shall observe all local and national electrical and building codes.

LI381 Corridor Light - LI382 Corridor Zone Light

The Alpha Communications® / TekTone **LI381** corridor dome light (with single white bulb) and **LI382** corridor zone lights (with 1-white and 1-red bulb) provide visual indication of any type of call when used with a nurse-call, emergency-call, or for stand-alone signaling applications.

When used with our **NC110A**, **NC110N**, **NC150N**, **NC150R** or **NC200N** series nurse-call systems, emergency calls are indicated by the rapid flashing of the **LI381** corridor dome light associated with the calling station. Normal (routine) calls produce a steady illumination. The **LI382** corridor zone light indicates an emergency call by the rapid flashing of the red lamp associated the zone or area from which an emergency call has been placed. Normal calls are indicated by a steady illumination of the white lamp. They can also be used with our **AlphaEcall™** and **CM800** series and other emergency-call and/or signaling system(s).

Both models mount on a standard 1 or 2-gang electrical back box and feature an easily removable white translucent cover for quick bulb replacement, without the use of any tools required.

Features

- U.L. 1069 Listed - 4th Edition Standards
- Operates on 24VAC or 24VDC
- Easy Bulb Replacement - No Tools Required
- Flame Retardant Fog White ABS Plastic Panel
- Excellent Visibility

Specifications

Dimensions:	Height: 4.56" (116mm) Width: 4.56" (116mm) Projects: 3.00" (76mm) from mounting surface
Bulb:	Type 1829, 28V, min. Bayonet Mt. (model# LI028)
Mounting:	Fits standard 1-gang or 2-gang box. Minimum depth of box to be no less than 1.75".
Finish:	Translucent white plastic cover mounted on a flame retardant, fog white ABS plastic panel.

42 Central Drive • Farmingdale • NY • 11735-1202 • Phone: (631) 777-5500 • Fax: (631) 777-5599
TOLL-FREE: (800) 666-4800 • Web: AlphaCommunications.com • Email: info@alphacommunications.com

Copyright© 1998-2014 Alpha Communications® - All Rights Reserved.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice. [Next \(APS062\) >](#)

[< Previous \(APS060\)](#)