

## DESCRIPTION

The Verifact™ "L-DT" Microphone is a desktop microphone that is designed for conducting interviews or similar applications. It contains two electret condenser microphones facing opposite directions that are mounted in a sturdy ABS plastic housing. Housing contains a weighted non-slip bottom for adherence to a desktop or flat surface. The Verifact™ L-DT is compatible with all Louroe Audio Base Stations.

## APPLICATION

When part of a Louroe Audio Monitoring System, Verifact "L-DT" Microphone can be used in situations such as

- Interview Rooms
- Speech Therapy Labs
- Cashier Booths
- Information Counters
- Where ceiling and wall mountings are not practical

## WIRING REQUIREMENTS

2 Conductor shielded cable, 22 gauge with a 24 gauge drain wire.

NOTE: Unshielded cable is not satisfactory for audio systems



### IMPORTANT NOTICE

When this equipment is used as part of an audio monitoring system, the law requires that the public be given notice of AUDIO MONITORING ON THE PREMISES. A decal notice is included with each microphone shipped.



### FEDERAL LAW REFERENCES:

Federal Regulations, US Code, Title 18. Crime and Criminal Procedure, Sec 2510.

**MANUFACTURED  
IN THE**



Verifact "L-DT" Microphone



## FEATURES

- Two opposing built-in microphones
- Low impedance, omni-directional pattern
- Contains pre-amp for line level output
- ABS Housing for long endurance
- May be located up to 1,000' from Louroe Base Station
- Weighted, non-slip bottom for firm adherence to desktop or any flat horizontal surface

## SPECIFICATIONS (Microphone - Verifact "L-DT")

■ Frequency response	40 Hz to 15 kHz ± 1 dB
■ Output	Line Level (0 dB @ 1000Ω)
■ Current drain	4 mA
■ Supply voltage	12 Vdc
■ Microphone housing	High impact ABS
■ Dimensions	4 3/4"L x 3"W x 1 3/4"H
■ Weight (net)	(7.5 oz ) (0.45 lbs) (0.20 kg)

## WARRANTY

LOUROE ELECTRONICS® warrants that at the time of shipment products manufactured by LOUROE ELECTRONICS to be free of defects in material and workmanship. Should a defect appear within one year (12 months) from date of shipment, LOUROE ELECTRONICS will, at its sole discretion, repair or replace the defective equipment. This equipment shall not be accepted for repair or return without prior notification by LOUROE ELECTRONICS.

This warranty does not extend to any Louroe product that has been subjected to improper or incorrect installation, misuse, accident, or in violation of installation instructions provided by LOUROE ELECTRONICS.

Returned shipments to LOUROE ELECTRONICS shall be at customer's expense. LOUROE ELECTRONICS will return the equipment prepaid via best way.