

PRODUCT FEATURES

- Bracket mounts easily using common
- · Internal wire access chamber
- · Automatic dual-voltage no field adjustment required
- · Instant release circuit no residual magnetism
- · Efficient, low power usage
- · All ferrous metal surfaces plated for durability and rust resistance
- MagnaCare® lifetime replacement, no fault warranty

PRODUCT OPTIONS

- (S) Senstat
- (D) Integrated door position switch (DPS)
- (L) LED indicator
- (T) Anti-tamper switch

SPECIFICATIONS

- UL 10C Listed
- CAN4-S104, CAN/ULC-S533 Listed
- · ANSI/UL 294 Listed
- CSA-C22.2 No.205 Listed
- ANSI/BHMA A156.23, Grade 1; E18501-500
- · CSFM- California State Fire Marshal Approved
- CE:EN 50081-1(92), EN 61000-6-2(99) Approved

Holding Force:

600 lbs [272kg]

Dimensions:

Magnalock: 10-1/2"Lx1-11/16"Dx2-1/2"H **Strike:** 6-1/4"L x 1/2"D x 1-5/8"H

Electrical:

350 mA at 12 VDC 170 mA at 24 VDC

Operating Temperature:


+32 to +110F [0 to +43C] Indoor use only

Shipping Weight:

8 lbs [3.63kg]

Finishes:

US28/628 - Brushed Aluminum







ASSA ABLOY, the global leader in door opening solutions

M38 SERIES


600 lbs Holding Force

Bracket Mounted with Easy Installation for Interior Applications

The M38 electromagnetic lock is ideal for traffic control in high-use areas within secured or monitored perimeters. Offerings include solutions for interior rooms, closets and hallways where reliability, high durability and lowmaintenance are required. Bracket mounting and wiring chamber provide quick, accurate installation.

>> MODELS		PART # Description
M38	Magnalock® Model 38	
M38D	M38, DPS	
M38DL	M38, DPS, LED	
M38DLS	M38, DPS, LED, Senstat	
M38DLST	M38, DPS, LED, Senstat, Tamper	
M38DS	M38, DPS, Senstat	
M38LS	M38, LED, Senstat	

For dress covers and flexible mounting brackets, see page 19.





FIRE RATED







17