

PRODUCT FEATURES

- Bracket mounting provides the easiest install for out-swing doors
- Innovative templating for an effortlessly accurate alignment between magnet and armature plate
- Sleek, low profile and refined lines for improved aesthetics
- LED shows red or green for lock status indication
- Autosensing dual voltage with microprocessor technology
- Wire chamber anti-tamper switch
- · Efficient, low power usage
- Size optimized for use with door closers
- MagnaCare Lifetime Replacement No Fault Warranty

PRODUCT OPTIONS

• Mounting for glass door applications

SPECIFICATIONS

- UL 1034 Burglary–Resistant Listed
- UL 10C Listed
- CAN4-S104, CAN/ULC Listed

- UL 294 Recognized Component
- ANSI/BHMA A156.23, Grade 1; E18501-1000
- CSFM- California State Fire Marshal Listed
- Patents: D682,655; D690,576
- Patents Pending

Holding Force:

1100lbs [499 kg]

Dimensions:

Magnalock: 11-1/2"L x 2-9/16"D x 2-1/2"H **Strike:** 9-1/2"L x 1/2"D x 2"H

Electrical:

575mA (± 10%) at 12VDC 275mA (± 10%) at 24VDC

Operating Temperature:

+32 to +110F [0 to +43C] Indoor use only

Shipping Weight:

13lbs [5.44kg]


Finishes:


US28/628 - Satin Aluminum Clear Anodized (Standard)

US20A/313 - Satin Brown Anodized

335 - Satin Black Anodized

600 - Paintable Primer Gray Finish







M670 SERIES

1100lbs Holding Force


The Simple, Stylish and Secure Magnalock®


The M670 from Securitron delivers unsurpassed style and ease of installation.

Style. The aesthetics of the M670 are refined enough for the most discriminating designer openings.

Easy installation. The fastest, easiest, most secure installation of any bracket-mount maglock.

>> MODELS		PART # Description
M670	M670 Magnalock, Satin Aluminum	
M670-313	M670 Magnalock, Satin Brown	
M670-335	M670 Magnalock, Satin Black	
M670-600	M670 Magnalock, Paintable Primer Gray Finish	
For bracket ontions, see page 34		











13