

89P SERIES MULTIMODE



Single Fiber Bi-directional Transceivers Audio and Contact Closure System Interface For Zenitel Intercom Systems - 9600 Series



FEATURES:

- Bi-directional Audio and Contact Closure Transceivers
- Diagnostics: Power and Optical Presence
- Voice Operated (VOX) Transmission
- FM Modulated Audio

SPECIFICATIONS:

Audio:

Bandwidth.....300 Hz to 10 KHz
 THD @ 1 KHz.....2%
 SNR.....50 dB
 Connector.....5 Pin Screw Terminal

Contact Closure:

InputSwitch Closure to Ground
 OutputDry Contact
 Response Time.....2 ms
 Connector.....5 Pin Screw Terminal

Optical:

Wavelength850/1300 nm
 Loss Budget (62.5/125µ).....12 dB
 Connector.....ST

Temperature (Operating):

-20°C to +70°C, non-condensing

Power Supply:

Module - 24 VAC Center Tap (AFI Part #: PS-24-CT-T)
 Rack Card - See AFI Part #: SR-20/2

Size:

Module - 5¾" x 6¾" x 1¾"
 Rack Card requires one rack slot - 6½" x 1" x 5"

ORDERING INFORMATION:

MT = Module Transmitter - Station
 MR = Module Receiver - Master
 RT = Rack Card Transmitter - Station
 RR = Rack Card Receiver - Master

Example: MT-89P to RR-89P



The American Fibertek 89P Series transmits one channel of high-quality low distortion bi-directional audio/contact closure on one multimode optical fiber. Designed to be completely transparent, the system field microphone and audio levels can be adjusted to balance and optimize signal levels. Diagnostic indicators provide a quick visual indication of system status. Equipment may be ordered as stand alone modules or rack cards that are mounted in the American Fibertek Card Cages: SR-20/2 or SR-20R/1.

