913C-SL SERIES SINGLEMODE

SINGLE CHANNEL DIGITAL VIDEO SYSTEM WITH THREE BI-DIRECTIONAL MULTI-PROTOCOL DATA CHANNELS

Features:

- ◆ Compatible with NTSC, (RS 170A & RS –343A), PAL and SECAM
- ◆ Diagnostics: Video, DC Power, Digital Frame Sync, OLI, Data Activity
- Available with Enhanced "Afinety" Intelligent Monitoring System
- ◆ 10 Bit Digital Video Transmission
- ◆ Serial Digital Transmission

Specifications:

Video:

I/0 Level	1 Vp-p (±3 dB)
I/0 Impedance	75 Ohms
Bandwidth	7 MHz
Differential Gain	2 %
Differential Phase	0.7 °
SNR (Unified Weighted)	65 dB
Connector	BNC

Data (3 Channels):

Number of Channels.	3 (Full Duplex)
Interface485(2 or 4	Wire)/RS422/RS232
Data Format	Asynchronous, Serial
Data Rate	DC to 115 Kbs
Connector5	Pin Screw Terminals

Optical:

Wavelength	1310/1550nm
Loss Budget (9/125µ)	21 dB
Connector	FC

Temperature (Operating)

-40°C to +75°C, non-condensing

Power Supply:

Module – 12 VDC (AFI Part # PS-12D) Rack Card – AFI SR 20/2

Size

Product Ordering Information:

MT-913C-SL Module Transmitter
MR-913C-SL Module Receiver
RT-913C-SL Rack Card Transmitter
RR-913C-SL Rack Card Receiver

10/18/12



The American Fibertek 913C-SL Series transmits one channel of high-quality 10 bit digitized video and three channels of multi-protocol data on one singlemode optical fiber using WDM technology. Designed to be completely transparent to all camera and monitor manufacturers, this system requires no field adjustments at installation or additional maintenance thereafter. Diagnostic indicators provide a quick visual indication of system status. The "Afinety" intelligent remote monitoring system is available on this product, please consult factory.

Equipment may be ordered as stand alone modules or rack cards that may be mounted in the American Fibertek Card Cages: SR-20/2 or SR-20R/1.

