

RS485/RS422 Data System - Two Channels

FEATURES:

- ◆ RS485 Two Channels 2 wire or 4 Wire Interfaces
- ◆ Switch Selectable 2W or 4W, Terminations and Line Bias
- ◆ DC to 115 Kb/s
- ◆ Activity Indicators for Data Tx and Rx for each Channel
- ◆ Only One Fiber Required
- ◆ Hot Swappable

SPECIFICATIONS:

RS485:

Data Rate: DC to 115 Kb/s
Connector Terminal Blocks

OPTICAL:

Wavelength:..... 1310/1550 nm
Source: Laser
Loss Budget (9/125 u) >21 dB
Connector: FC/PC

POWER:

Voltage 12 VDC
Current < 350mA
Connector..... 2 Pin Terminal Block

Power Supply:

Module 12VDC (AFI Part #: PS-12D)
Rack Card (AFI Part #: SR-20/2)

PHYSICAL:

Temperature..... -20 to 70 °C
Humidity 5 to 95 %

Size:

Module 4¼" x 4¼" x 1⅛"
Rack Card - One Slot 6½" x 5" x 1"



The American Fibertek 487SL Series transmits and receives two channels of RS485 data (2 wire or 4 wire user configurable) or RS422 data or 1 of each over a single singlemode optical fiber. The system is comprised of two transceivers forming a point-to-point communications link. The system is designed to be completely transparent to data protocol. For ease of installation, diagnostic indicators provide a quick visual indication of system status. Equipment may be ordered as stand alone modules or rack cards that are mounted in the American Fibertek Card Cages: SR-20/2 or SR-20R/1.

ORDERING INFORMATION:

MTX-487-SL = One Fiber Module Singlemode FC Connectors 1310nm Tx
MRX-487-SL = One Fiber Module Singlemode FC Connectors 1550nm Tx
RTX-487-SL = One Fiber Rack Card Singlemode FC Connectors 1310nm Tx
RRX-487-SL = One Fiber Rack Card Singlemode FC Connectors 1550nm Tx