



PK305A Supplemental Power Supply

IL698 Specification Sheet

Tek-CARE®NC300II Nurse Call System • Rev. 6 - 07/2013

Features

- Plug-in connectors for easy connection to NC351A/2 Central Equipment
- Provides additional power to the NC351A/2 Central Equipment to support 512 patient stations
- UL® 1069 Listed

Description

The PK305A Supplemental Power Supply is used to provide additional power to the NC351A/2 Central Equipment to support 512 patient stations.

The supplemental power supply is housed in a durable metal enclosure with provisions for plug-in field wiring connections.

Listings



UL® 1069 listed; UL® File Number E71599.



PK305A Supplemental Power Supply

Specifications

Dimensions:	Console: 10.75" × 8.75" × 3.25"
Power Input:	115 VAC, 60Hz, 140W
Environments:	26°C, maximum 80% relative humidity
Terminations:	Plug-in connectors
System Protection:	In-line fuses are provided on primary input

Required Components

Tek-CARE®NC300II Nurse Call System
with NC351A/2 Central Equipment

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3

TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)