



# PK502B Dual Entrance Control Unit

## IL955 Specification Sheet

Tek-ENTRY® Apartment Entry Systems • Rev. 0 - 04/2013

### Features

- Provides access control to multiple entrances on one apartment entry system
- Use with PK543A speaker systems or PK205 handset systems
- Transfers both door release function and audio between entrance panels
- Powered by the intercom system amplifier
- Polarized plug-in color-coded pigtailed connector
- Built-in test circuit with LED display
- Surface mounted
- Small footprint

### Description

The TekTone® PK502B Dual Entrance Control Unit provides a means to transfer apartment intercom panel and door release operations between more than one entrance. Pressing a call button on an entrance panel automatically transfers the voice and door release functions to that entrance. All PK502B control units are located at the amplifier location and do not need to be spread out.



PK502B Dual Entrance Control Unit

### Specifications

Dimensions:	Height:	5.5" (140 mm)
	Width:	3.125" (80 mm)
	Depth:	2" (51 mm)
Construction:	Flame-retardant (UL® 94V-0) plastic	
Connections:	Polarized plug-in type	
Mounting:	Surface mount	

### Required Components

PK543A Amplifier/Relay/Power Supply  
-or-  
PK205 Amplifier/Relay/Power Supply

[www.tektone.com](http://www.tektone.com)

277 Industrial Park Road • Franklin, NC 28734 • [tektone@tektone.net](mailto:tektone@tektone.net)

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3  
TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)