



PK505 Power Supply

IL895 Specification Sheet

Tek-CARE® Nurse Call Systems • Rev. 1 - 08/2013

Description

The PK505 is a class 2 plug-in power supply. It is powered by 110VAC and its output supplies 12VDC with a minimum capacity of 1 amp. The PK505 has a 2-pronged non-polarized plug, so that it can plug into any standard outlet. It includes a 6-foot 22-gauge stranded wire whip.

Specifications

Transformer

Dimensions: 2.675" × 2.25" × 4.25"
(68 mm × 57 mm × 108 mm)

Wire Whip: 6' (1.83 m), 22-gauge stranded,
2 conductor

Required For Use With

Tek-CARE® 500 Wireless Emergency Call System:

- NC505ES Remote LCD Receiver—16 points, 6 outputs
- NC506ES Remote Receiver—4 points, 4 outputs
- NC507ES Remote LCD Receiver—32 points, 12 outputs

Tek-CARE® NC300II Nurse Call System:

- NC367 Wireless Receiver with Momentary Contact

Tek-CARE® NC110, NC150 or NC200 Nurse Call Systems:

- NC267 Wireless Receiver with Latching Contact



PK505 Power Supply

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3
TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)