



SS102A and SS106 Transformers

PO001 Electric Door Opener

IL127 Specification Sheet

Rev. 14 - 04/2013



SS102A



SS106

SS102A and SS106 Transformers



PO001 Electric Door Opener

Transformer Features

TekTone®'s SS102A and SS106 Class 2 Transformers offer compact, easy-to-install low voltage AC power sources for use with various TekTone® intercom systems. Both transformers are UL® Listed Class 2 transformers and will safely take themselves offline when overheated.

The transformers are constructed for easy surface installation or in a standard 1/2" knockout, and may be used in plastic or metal boxes. Primary wire connections are made using the pre-stripped pigtailed and ground wire; secondary connections are made using screw terminals.

Specifications

| | |
|--------|---|
| SS102A | 120 VAC primary, 16 VAC 10 VA secondary |
| SS106 | 120 VAC primary, 8 VAC 20 VA 16/24 VAC 30 VA secondary |

Electric Door Opener Features

TekTone®'s PO001 Electric Door Opener is for use in unlocking and locking doors from a variety of TekTone® remote stations. The door opener can be installed in place of the door lock, or on a door jamb with various door locksets.

The PO001 is a normally locked type with heavy duty coils, and operates on 8-16 VAC or 3-6 VDC. The unit features a flat face with satin zinc finish and solid brass locking latch for long wear. The PO001 is reversible for mortise-type locks and latches up to 1/2" width and throw, and is ideal for most narrow jamb mortise-type installations. Depending on the specific job requirements, the PO001 can be reversed for right or left-hand door installation.

Dimensions

| | | |
|----------------|----------------|--------------------|
| Faceplate: | 1.25" × 5.875" | (31.8 mm × 149 mm) |
| Case width: | 0.9375" | (24 mm) |
| Case depth: | 1.4375" | (37 mm) |
| Latch opening: | 1.375" | (35 mm) |

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3
TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)