



# R2416ULi Isolated Rack Mount CCTV Power Supply

Rev. DSR2416ULi\_10252012



R2416ULi

## **Overview**

R2416ULi provides 24VAC distributed via sixteen (16) isolated fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

## **Specifications**

### ***Input:***

- 115VAC, 50/60Hz, 5.4 amp.

### ***Output:***

- Sixteen (16) isolated fuse protected outputs.
- 24VAC @ 25 amp (600VA) supply current (1.6 amp per device, 3.5 amp max.)
- Outputs are rated @ 3.5 amp.
- Surge suppression.

### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- 227 BTU/Hr.
- System AC input VA requirement: 690VA.

### ***Features:***

- Sixteen (16) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- 3-wire grounded line cord.
- Removable terminal blocks with locking screw flange.
- Spare fuses provided.

### ***Mechanical:***

- 2U rack mount chassis for use in standard EIA 19" rack.
- Enclosure Dimensions (H x W x D approx.): 3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm)
- Product weight (approx.): 24.4 lbs. (11.07 kg).
- Shipping weight (approx.): 25.4 lbs. (11.52 kg).

## **Agency Approvals**



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

**Enclosure Dimensions (H x W x D approximate):**  
 3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm)

