

RA-4961-MCQ

Wireless Magnetic Contact

Features:

- For use with the RA-4961 series receivers
- Wirelessly monitor windows, doors, or other areas
- Up to 1,000ft (305m) transmission range*
- Activates each time the door or window is moved
- Magnet can be placed on either side
- Adhesive mount – no screws required



RA-4961-MCQ

Specifications:

Model Number		RA-4961-MCQ
Frequency		914.8MHz
Transmission range*		Up to 1,000ft (305m)
Channels		1
Power supply		2x CR2032 Batteries (Included)
Current Draw	Standby	8µA
	Max	80mA
Estimated battery life		132 days (3 triggers/day)
Low battery indicator		Zone LED on receiver blinks continuously
Sound level		96dB@1ft(30cm)
Contact distance		³ / ₈ "(1cm)
Operating Temperature		-4°~140°F (-20°~60°C)
Dimensions	Magnetic Contact	1 ⁷ / ₈ "x1 ¹ / ₄ "x4 ³ / ₁₆ " (48x7x107mm)
	Magnet	³ / ₈ "x1 ¹ / ₄ "x1 ⁹ / ₁₆ " (10x7x39mm)

* Line of sight. Transmission range will vary depending on installation and operating environment.

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com



Copyright 2015 © SECO-LARM U.S.A., Inc. All rights reserved.
All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners.
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA SLI®

PI_RA-4961-MCQ_151210.docx