ENFORCER Security

High-Intensity LED Modules

SL-1311-MA SL-1302-MA High Intensity 1Wx4 LED Module 52 LED Disk Module

19 Programmable Flash Patterns

Features:

- ► Connect to the outside of an alarm bell box for external high-intensity notification.
- ► Fully epoxied weatherproof (IP66) and vibrationresistant design for external or internal use.
- ▶ Up to 100,000 hours of continuous use.
- ▶ 19 Built-in programmable flash patterns.
- ▶ Up to 15 units can be synchronized to flash simultaneously or alternately.
- ► Multi-voltage input: 10~30VDC.
- ▶ Non-volatile memory recalls last flash pattern used at power-up.
- ▶ Surface mounting or flush mounting.

Sample Applications:

- ▶ Visual indicator for security systems
- ► Caution and hazard lighting
- ▶ Police and security vehicles
- ▶ Fire trucks
- ▶ Construction vehicles
- Ambulances

Specifications:

	SL-1311-MA	SL-1302-MA
Housing shape	Rectangular	Circular
# of LEDs	4 High-intensity 1W LEDs	52 High-intensity LEDs
Max. current draw	560mA@12VDC	640mA@12VDC
	300mA@24VDC	320mA@24VDC
Operating voltage	10~30VDC	
Electrical protection	Reverse polarity protected	
Operating life	LEDs rated at 100,000 hours (>11 years)	
# of flash patterns	19 (Programmable)	
Synchronization	Sync or alternate up to 15 units	
IP Rating	IP 66	
Operating temperature	-22°~150° F (-30°~65° C)	
Dimensions	4 ¹ / ₂ "x1 ¹ / ₄ "x1 ³ / ₁₆ "	4 ¹ / ₄ "x1 ¹ / ₄ "
	(122x31x30 mm)	(109x31 mm)



SL-1311-MA





Available in 4 Different Colors:

LED Color	Model 🚥	Model 🔘
Clear	SL-1311-MA/ C	SL-1302-MA/ C
Red	SL-1311-MA/ R	SL-1302-MA/ R
Blue	SL-1311-MA/ B	SL-1302-MA/ B
Amber	SL-1311-MA/ A	SL-1302-MA/ A

SECO-LARM®

16842 Millikan Avenue Irvine, CA 92606 Tel: 1-949-261-2999

1-800-662-0800 Fax: 1-949-261-7326 Web: www.seco-larm.com

Email: info@seco-larm.com

Copyright © 2010 SECO-LARM U.S.A, Inc. All rights reserved