SECO-LARM
Connector Series

- All DC plug dimensions are 5.5 (OD) x 2.1mm.
- All DC jack dimensions are 5.5 x 2.1mm.
- All DC plugs and jacks come with UL-listed AWG#22 wires.
- LED color legend for illuminated DC plugs and jacks.
  Blue light → DC powered
  Red light → DC wrong polarity
  Purple light → AC powered

- Maximum allowable current: 2 Amp.
- Maximum allowable voltage: 30 VAC / VDC.
- "LED" indicates PATENTED illuminated version.
- Polarity configuration for all DC plugs and jacks: "— ⊙ ± ."

CA-171T-02Q
RJ45 male to terminal block with 2" cable

EVA-CB0R1
Gold plated BNC to RCA connector

EVA-WB0B1-08
8" male-to-female gold plated BNC connector

EVA-RS1
RS-232 to RS-485 converter

EVA-F5521-3
DC plug with 3-ft. pigtail wire

EVA-M5521-3
DC jack with 3-ft. pigtail wire

CA-1610-3FLQ [Patented]
LED-illuminated DC plug with 3-ft. pigtail wire

A-1510-3FLQ [Patented]
LED-illuminated DC jack with 3-ft. pigtail wire

CA-161T-02SQ
DC plug tosnap-in terminal block with 2.5" wire

CA-151T-02SQ
Snap-in DC jack to terminal block with 2.5" wire

CA-161T-02SLQ [Patented]
LED-illuminated DC plug to snap-in terminal block, with 2.5" wire

CA-151T-02SLQ [Patented]
LED-illuminated DC jack to snap-in terminal block, with 2.5" wire

CA-1615-06LQ [Patented]
LED-illuminated DC plug to DC jack

CA-1526-1FQ
Single DC jack to double DC plugs

CA-1536-1FQ
Single DC jack to triple DC plugs

CA-1616Q
DC plug-to-DC plug adapter

CA-1515Q
DC jack-to-jack adapter

CA-161R
DC Plug-to-terminal block