



# SF117/2C, SF117/4C Emergency Switch

## IL178 Specification Sheet

CM800 Emergency Call Systems • Rev. 14 - 12/2013

### Features

- Single-gang mounting
- 2 or 4 pole switches
- Attractive, flame-retardant (UL® 94V-0) plastic panel
- Highly visible emergency labeling
- May use with a central annunciator, or for local alarm functions

### Description

The SF117-series Emergency Call Switch is available in two models and features a rugged, long-life, positive-acting switch mounted on a durable flame-retardant (UL® 94V-0) plastic panel. Signaling an emergency requires just a short pull in any direction on the 6' long nylon cord. The signal cannot be canceled except at the point of origin. The SF117/2C provides two circuits to operate a separate visual and audible signal. The SF117/4C provides two additional circuits that may be used to operate additional signaling devices as needed.

### Specifications

|             |                                     |       |          |
|-------------|-------------------------------------|-------|----------|
| Dimensions: | Height:                             | 4.5"  | (114 mm) |
|             | Width:                              | 2.75" | (70 mm)  |
|             | Depth:                              | 1.5"  | (38 mm)  |
| Panel:      | Flame-retardant (UL® 94V-0) plastic |       |          |
| Switch:     | SF117/2C—2PDT                       |       |          |
|             | SF117/4C—4PDT                       |       |          |
| Connection: | Wire leads                          |       |          |
| Mounting:   | Standard single-gang electrical box |       |          |
| Marking:    | Pad-printed <b>EMERGENCY</b>        |       |          |



SF117/2C, SF117/4C Emergency Switch

### Required Components

#### Standalone:

- SS106 Transformer
- LI381 or LI123B Corridor Dome Light

#### System:

- CM800 Emergency Call System

[www.tektone.com](http://www.tektone.com)

277 Industrial Park Road • Franklin, NC 28734 • [tektone@tektone.net](mailto:tektone@tektone.net)

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3

TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)