



SF337C Emergency Shower Switch

IL629 Specification Sheet

Tek-CARE® Nurse Call Systems • Rev. 12 - 11/2012

Features

- UL® 1069 Listed
- Waterproof if installed per manufacturer's instructions
- Call-placed indicator
- Call cancel at point of origin
- Attractive, flame-retardant (UL® 94V-0) plastic faceplate
- 1.1" (28mm) wide pull-down lever
- Washable TPU plastic pull cord kit is included

Description

The SF337C Emergency Shower Switch is for any location where activation of an emergency signal is required. The design is such that it may be located anywhere in a shower, bath or tub room, regardless of environmental conditions. The combination of rubber-grommetted mounting screws, rubber mounting gasket, and completely sealed front faceplate make it waterproof (if properly installed). Electronic components are mounted on a circuit board, including an industry-proven reliable reed switch for circuit initiation. The activating magnet is mounted on the large pull-down lever, which is completely sealed in plastic. The indicator LED is also completely sealed.

Due to the flexibility of its design, the SF337C may be used as a pull cord or as a pull down activated emergency switch. The pull cord supplied may be used for emergency call activation, or if desired, the large 1.1" (28 mm) red pull-down lever may be used. Dome light and system annunciation vary according to the manner in which the SF337C is connected.

Listings



UL® 1069 listed; UL® File Number E71599.



SF337C Emergency Shower Switch
(cord not shown)

Specifications

Dimensions:	Height:	4.5"	(114 mm)
	Width:	2.8125"	(72 mm)
	Depth:	1.625"	(41 mm)
	Projects:	0.6875"	(17 mm) (including pull down lever)
Construction:	Flame-retardant (UL® 94V-0) plastic		
Connections:	Plug-in type.		
Housing:	Single gang ring with square box.		

Applicable Systems

Tek-CARE®400 P5 Nurse Call System
Tek-CARE®NC300II Nurse Call System
Tek-CARE® NC200, NC150, NC110 Nurse Call Systems
Tek-CARE®500 Wireless Emergency Call System

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3

TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)