



# SF340B Emergency Switch

## IL509 Specification Sheet

Tek-CARE®400 P5 & NC300II Nurse Call Systems • Rev. 17 - 11/2012

### Features

- UL® 1069 Listed
- Simple and flexible operation
- Call-placed indicator
- Call cancel at point of origin
- Flame-retardant (UL® 94V-0) plastic faceplate
- 1.1" (28 mm) wide pull-down lever
- Washable TPU plastic pull cord kit is included

### Description

The SF340B Emergency Switch is for use in any location where activation of an emergency signal is required. All electronic components are mounted on a circuit board. The specially mounted LED is completely sealed in plastic.

Due to the flexibility of its design, the SF340B may be used as a pull cord emergency switch, a pull down activated emergency switch, or a staff assist emergency call switch. The pull cord supplied may be used for emergency call activation or, if desired, the large 1.1" (28 mm) red pull-down lever may be used.

Dome light and system annunciation vary according to the manner in which the SF340B is connected.

### Specifications

Dimensions:	Height:	4.5"	(114 mm)
	Width:	2.8125"	(72 mm)
	Depth:	1.625"	(41 mm)
	Projects:	0.6875"	(17 mm)
		from mounting surface (including pull-down lever)	
Construction:	Flame-retardant (UL® 94V-0) plastic faceplate. Switch and electronic components are circuit board mounted.		
Connections:	Plug-in connectors.		
Housing:	Single gang ring (IH357) with square box (IH358), or exact equal.		



SF340B Emergency Switch  
(pull cord not shown)

### Listings



UL® 1069 listed; UL® File Number E71599.

### Applicable Systems

Tek-CARE®400 P5 Nurse Call System  
Tek-CARE®NC300II Nurse Call System

[www.tektone.com](http://www.tektone.com)

277 Industrial Park Road • Franklin, NC 28734 • [tektone@tektone.net](mailto:tektone@tektone.net)

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3  
TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)