



SF401A Oxygen-Safe Call Cord IL767 Specification Sheet

Tek-CARE®400 P5 Nurse Call System • Rev. 5 - 11/2012

Features

- UL® 1069 Listed
- Oxygen safe
- Impact resistant and waterproof
- Small, lightweight pendant fits comfortably in hand
- Bed clips included

Description

The TekTone® SF401A single call cord is for use with the Tek-CARE®400, Tek-CARE®400 P5, and Tek-CARE®NC300II nurse call systems, where 8-pin DIN jacks are used. The SF401A is an oxygen safe call cord that is certified safe for use by all patients receiving oxygen therapy. This waterproof and impact resistant call cord has a completely sealed push button.

Listings



UL® 1069 listed; UL® File Number E71599.

Specifications

Connection: 8-pin DIN plug
Construction: SPST1-A switch
Integral brass, fine silver contacts
1 AMP, 115 watt maximum, AC
Dimensions: 7' (2.13 m) long polyvinyl-covered cord



SF401A Oxygen-Safe Call Cord

Required Components

for the Tek-CARE®400 nurse call system:

IR411, IR411EPB, IR412, IR412EPB patient stations

for the Tek-CARE®400 P5 nurse call system:

IR411P5, IR412P5 patient stations

for the Tek-CARE®NC300II nurse call system:

IR319B, IR320B patient stations

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3
TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)