



# SF401G Call Cord

## IL829 Specification Sheet

Tek-CARE®400 P5 Nurse Call System • Rev. 2 - 11/2012

### Features

- Sensitive touch activation
- Oxygen tent safe
- Ideal for geriatric use
- Momentary, air-activated switch
- Adjustable bed clip

### Description

TekTone® SF401G Call Cords are used with 8-pin DIN jack patient stations, including Tek-CARE®400 IR411- and IR412-series patient stations, Tek-CARE®400 P5 IR411P5 and IR412P5 patient stations, and Tek-CARE® NC300II IR319- and IR320-series patient stations.

The SF401G Call Cord is specifically designed for use in geriatric and oxygen environments, but may also be used in general applications. To place a call, the patient need only apply slight pressure to the squeeze bulb using any part of the body. The force of air through the vinyl tubing closes a switch in the plug, thus placing a call. An adjustable bed clip is supplied for the SF401G and is attached to the call cord.

### Listings



UL® 1069 listed; UL® File Number E71599.

### Specifications

Switch:	Momentary contact, air activated		
Plug:	Stainless steel 8-pin DIN		
Cord:	Vinyl tubing		
Electrical:	Rated current 1/3 amp, 24 VAC-VDC		
Dimensions:	Cord:	6' long	(1.83 m)
	Bulb:	1.5" diameter	(38 mm)



SF401G Call Cord

### Required Components

*for Tek-CARE®NC300II Nurse Call Systems:*  
IR319- or IR320-series Patient Stations

*for Tek-CARE®400 Nurse Call Systems:*  
IR411- or IR412-series Patient Stations

*for Tek-CARE®400 P5 Nurse Call Systems:*  
IR411P5 or IR412P5 Patient Stations

[www.tektone.com](http://www.tektone.com)

277 Industrial Park Road • Franklin, NC 28734 • [tektone@tektone.net](mailto:tektone@tektone.net)

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3  
TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)