

4-Channel RF Transmitters and Receiver

SK-919TP4J-NUQ SK-917TP4J-NU

4-Button Pre-Coded Transmitter 4-Button CODEBUMP[™] Transmitter

- Range: Up to 500ft (152m)*, 315MHz
- LED Transmission indicator
- Attractive slimline design
- Over 68 billion possible codes
- Includes 12VDC alkaline battery
- Compatible with all 315MHz SECO-LARM receivers
- SK-917TP4J-NU: Code changes every time transmitter button is pressed

SK-919TP4H-NUQ 4-Button Handheld Transmitter

- Range: Up to 500ft (152m)*, 315MHz
- Attractive slimline design
- Over 68 billion possible codes
- Includes two 3VDC lithium batteries
- Compatible with all 315MHz SECO-LARM receivers
- Visor clip and belt clip included. Belt-clip holster and wall-mount bracket also available (model #: SK-9HBC)
- Low battery indicator LED flashes when battery drops below 2VDC

SK-910R4Q

4-Channel Receiver

- Five programmable relay output modes:
 - Timed
 - Momentary (1, 2, 3, 4, 5, 10, 30, or 60 sec)
 - Toggle (ON/OFF)
 - Latch
 - Validity
- 11~24 VAC/VDC Operation
- Range: Up to 500ft (152m)*, 315MHz
- Independently programmable outputs
- Controls garage doors, gates, house lights, alarm panels or other devices via remote
- Four LEDs indicate RF reception, learn mode entered, transmitter learned, memory cleared, and relay output mode
- Pushbutton programming, no need to cut jumpers
- Up to 15 transmitter button codes per channel can be learned
- Compatible with all 315MHz SECO-LARM transmitters

*Actual range will vary greatly depending on the installation and operating environment

SECO-LARM[®] U.S.A., Inc.

16842 Millikan Ave, Irvine, CA 92606 Tel: 949-261-2999 / 800-662-0800 • Fax: 949-261-7326 sales@seco-larm.com • www.seco-larm.com



SK-910R4Q

Also Available from SECO-LARM[®]:

SK-91ERSD		
Increase range up to 1,000ft		
(304m)* with the Extended		
Range Antenna		



SK-910R4Q Specifications:

Operating frequency		315MHz
Memory capacity		15 Transmitter button codes per
		channel, 60 total
Operating voltage		11~24 VAC/VDC
Operating	Standby	8mA@12VDC
current	Active	30mA@12VDC
Relay contact rating		Form C 10A@24VDC/120VAC
Connectors		Screw terminals: Power (+,-), 1 relay per channel (NO/NC/COM)
Dimensions		5 ⁵ / ₁₆ "x3 ¹⁵ / ₁₆ "x1 ¹ / ₈ " (135x100x28 mm)



Copyright 2013 © SECO-LARM U S A, Inc All rights reserved The SECO-LARM policy is one of continual development For that reason, SECO-LARM reserves the right to change prices and specifications without notice SECO-LARM is not responsible for misprints

SECO-LARM[®] ENFORCER[®] CRIMEBUSTER[®] CBA SLI J

PiSK-910R4Q.docx



Wireless



SK-919TP4H-NUQ