

MODEL SLP-1L MONITORING/CONTROL STATION



SPECIFICATIONS

- DESIGNED TO RELEASE OR SECURE AND MONITOR ONE ELECTRIC LOCK
- ONE 1/2" RED LED OPERATES ON 12 OR 24 VOLTS AC OR DC
- ONE D.P.D.T. ILLUMINATED LATCHING PUSHBUTTON WITH HI-BRIGHTNESS BUILT-IN LED
- SWITCH LED OPERATES ON 12 OR 24 VOLTS AC OR DC
- SWITCH CONTACTS RATED 3 AMPS @ 35 VDC OR 120 VAC
- COMPONENTS MOUNTED ON STANDARD SINGLE GANG ELECTRICAL WALLPLATE
- SWITCH AND LED TERMINATED WITH COLORED LEADS
- GREEN AND YELLOW LEDS ARE AVAILABLE
- CUSTOM SWITCH LEGENDS ARE AVAILABLE
- ORDER MODEL SLP-1M FOR SWITCHES WITH MOMENTARY CONTACTS



ALARM CONTROLS CORPORATION

19 BRANDYWINE DRIVE P.O. BOX 280

DEER PARK, NY 11729

1 631 586-4220 1 800 645-5538

WWW.ALARMCONTROLS.COM EMAIL INFO@ALARMCONTROLS.COM

SLP WIRING INSTRUCTIONS

SWITCH LED

OPERATES ON 12 OR 24 VOLTS
AC OR DC

YELLOW LEAD	POSITIVE
BLACK LEAD	NEGATIVE

SWITCH

RED LEAD	N/C CONTACT
BLUE LEAD	N/O CONTACT
WHITE LEAD	COM CONTACT

LED

FOR 12 VOLT OPERATION

WHITE LEAD	POSITIVE
BLACK LEAD	NEGATIVE

FOR 24 VOLT OPERATION

RED LEAD	POSITIVE
BLACK LEAD	NEGATIVE



ALARM CONTROLS CORPORATION