



SAMSUNG TECHWIN

SMT-4030/3230

Monitors the choice of professionals



SMT-4030/3230

40"/32" LED Monitor

- Super high resolution 600TV lines
- High contrast ratio 5000:1
- Fast response time 8ms
- HDMI, VGA, and Composite video output
- Built-in Speaker
- Ethernet/RS-232C remote control
- Magicinfo Lite : scheduling function auto play function

The SMT-4030/3230 are 40"/32" monitors with Full HD a native 1920x1080 panel resolution optimized for CCTV applications. Benefiting from the latest onboard LED panel technology that offers excellent picture quality along with a fast 8ms response time. Offering 600TV lines high resolution and various video output via HDMI, VGA and composite, the SMT-4030/3230 is the perfect professional security monitor.




Specifications


| | SMT-4030 | SMT-3230 |
|--------------------------|--|--|
| DISPLAY | | |
| Type | LED | |
| Screen Size | 40" | 32" |
| Max. Resolution | 1,920 x 1,080 | |
| Brightness | 350cd/m ² | |
| Contrast Ratio | 5,000 : 1 | |
| Aspect Ratio | 16 : 9 | |
| Viewing Angle (H/V) | 178° / 178° | |
| Display Color | 16.7million | |
| Response Time | 8ms (G to G) | |
| Video System | NTSC / PAL | |
| Panel Life | 16 hours (daily use) | |
| Filter Type | 3D combfilter | |
| INTERFACE | | |
| Video | Connector | CVBS, HDMI, Component (D-sub 15pin) |
| | Connector | Analogue D-sub, DVI-D, Display port |
| RGB / DVI | Input Signal | 0.7Vp-p ±5% |
| | Available Format | 640 x 350@70Hz, 720 x 400@70Hz 640 x 480@60Hz/72Hz/75Hz (VGA) 800 x 600@56Hz/60Hz/72Hz/75Hz (SVGA) 1,024 x 768@60Hz/70Hz/75Hz (XGA) 1,152 x 864@75Hz, 1,152 x 870@75Hz 1,280 x 960@60Hz, 1,280 x 1,024@60Hz/75Hz (SXGA) 1,360 x 768@60Hz, 1,600 x 1,200@60Hz 1,920 x 1,080@60Hz |
| HDMI | Connector | HDMI |
| | Available Format | 640 x 480p@60Hz, 720 x 480i@60Hz, 720 x 480p@60Hz 720 x 576i@50Hz, 720 x 576p@50Hz, 1,280 x 720p@50Hz/60Hz 1,920 x 1,080i@50Hz/60Hz, 1,920 x 1,080p@50Hz/60Hz |
| Audio | Connector | RCA (L/R), Stereo mini jack |
| | Output Signal | Loop-through line level (PC only), Speakers : 2 x 5W |
| Application Support | Remote controller | |
| ON SCREEN DISPLAY | | |
| Functions | VESA™ DPM compatible | |
| Language | English, Spanish, French, German, Italian, Russian, Swedish, Turkish, Taiwanese, Chinese, Japanese, Korean | |
| GENERAL | | |
| Electrical | Input Voltage | 100 ~ 240V AC (50/60Hz) |
| | Power Consumption | Type 108W |
| Environmental | Operating Temperature | 0 ~ +40°C (+32°F ~ +104°F) |
| | Operating Humidity | 10% ~ 80% (Non-condensing) |
| Mechanical | Dimensions with Stand (WxHxD) | 925.4 x 611.0 x 311.0mm (36.43" x 24.06" x 12.24") |
| | Dimensions without Stand (WxHxD) | 925.4 x 541.0 x 93.7mm (36.43" x 21.3" x 3.69") |
| | Bezel Size | 17.5mm (0.69") |
| | Weight | 9.3Kg (20.5 lb) |
| Accessory | Cabinet Color | Black |
| | Rack Mounts | Optional |
| | VESA Mounts Interface | 200 x 200mm |
| | Accessory | SBM-320ST |

Dimensions

Unit : mm (inch)



Accessory (optional)



Foot Stand SBM-320ST



The Eco mark represents Samsung Techwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive.

Design and specifications are subject to change without notice.

DISTRIBUTED BY



SAMSUNG TECHWIN CO., LTD. 701, Sampyeong-dong, Bundang-gu, Seongnam-si, Gyeonggi-do Korea 463-400
Tel : +82-70-7147-8741~8749, 8752-8760 Fax : +82-31-8018-3745 www.samsungsecurity.com www.samsungcctv.com

SAMSUNG TECHWIN AMERICA INC.
100 Challenger Rd. Suite 700 Ridgefield Park, NJ 07660
Toll Free : +1-877-213-1222 Direct : +1-201-325-6920
Fax : +1-201-373-0124

SAMSUNG TECHWIN EUROPE LTD.
2nd floor No5, The Height, Brookland, Weybridge,
Surrey, U.K. KT13 0NY
Tel : +44-1932-82-6700 Fax : +44-1932-82-6701

SHANGHAI SAMSUNG TECHWIN CO., LTD.
32F, BIK B, International Business Center, No. 391
Guiping Rd., Shanghai, China, 200233
Tel : +86-21-5427-1155 Fax : +86-21-5423-5122



SAMSUNG TECHWIN