


Intense Light Miniature Weather/Vandal/Tamper Resistant Color Dome Camera with Chameleon Cover™

CILT13D1G 2.8 - 12mm auto iris varifocal lens, dark grey housing
CILT13D7G 3.6mm fixed lens, dark grey housing

Features

- 1/3" Sony Super HAD II™ CCD
- 620 TV lines of resolution
- Amplify existing light with no distance limitations
- Minimum illumination 0.00001 lux (intense light @ 256x)
- Day/Night camera without using IR LEDs
- Chameleon Cover™ - snaps on and can be painted to match any décor!*
- 3-axis wall or ceiling mount
- Full OSD operation
- 12VDC / 24VAC dual voltage operation
- Vandal resistant operation: can withstand hits from a 10 lb. sledgehammer!
- Tamper resistant operation: tamperproof screws for enhanced security
- Weather resistant operation: good for indoor or outdoor usage
- IP66 compliant
- 5 year warranty



Specifications

Image Sensor 1/3" Sony Super HAD II™ CCD
Resolution..... 620 TV lines
Minimum Illumination..... 0.00001 lux (intense light @ 256x)
Total Pixels 811 (H) x 508 (V)
Effective Pixels 768 (H) x 494 (V)
Scanning System..... 2:1 interlace
Synchronization Internal
OSD..... Available
Backlight Compensation..... BLC / HLC / D-WDR
S/N (Y signal) 52dB (AGC Off, weight on)
White Balance ATW / Manual / Set
Electronic Shutter Speed..... Auto: (1/60 sec. - 1/100,000 sec.)
Sense-Up..... Off / Auto (selectable limit x2 - x256)
AGC..... High / Middle / Low / Off

3DNR..... Auto / High / Middle / Low / Off
Motion Detection..... On / Off (4 zone)
Privacy..... On / Off (8 zone)
Mirror Off / Mirror / V-Flip / Rotate
Sharpness 0 - 30 (level adjustable)
Day/Night..... Color / BW / Auto / Ext
Power Supply 12VDC / 24VAC dual voltage operation
(power supply not included)
Power Consumption 12VDC, 150mA / 24VAC, 80mA
Operating Temperature/
Humidity..... -4° F – 122° F / RH 90% max.
Dimensions..... 3.07" (H) x 4.33" (Dia.)
Weight 1.54 lbs.

*Chameleon Cover™ - for best results when used outdoors, waterproof paint is recommended. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 12/9/13

Optional Accessories



PSW4
24VAC
Power Supply



PSW5
12VDC
Power Supply

