

Intensifier3® Series Indoor/Outdoor Vandal Resistant Dome Camera with Chameleon Cover™

See Color In Almost Complete Darkness Without IR LEDs

- HT7246iHR** 2.8 -12mm auto iris varifocal lens, dark grey housing
- HT7247iHR** 9 - 22mm auto iris varifocal lens, dark grey housing
- HT7250iHR** 5 - 50mm auto iris varifocal lens, dark grey housing


Features

- 1/3" Sony Super HAD II™ CCD
- 650 TV lines of color resolution
- Amplify existing light with no distance limitations
- No problems caused by objects that reflect or absorb IR light sources
- Heater circuitry eliminates fog or condensation under any weather condition
- Minimum illumination 0.00002 lux (Intensifier3® @ 512x)
- Chameleon Cover™: snaps on and can be painted to match any décor!*
- 12VDC / 24VAC dual voltage operation
- Full OSD operation
- Now with Presets: Outdoor, Indoor, Elevator, Lobby, Hallway & Dark
- 3 axis lens mount
- Vandal resistant operation
- Weather resistant operation
- IP66 compliant
- Relay outputs for motion detection
- 5 year warranty

**INT
3**



Shown with included paintable, snap-on *Chameleon Cover™



Specifications

Image Sensor.....	1/3" Sony Super HAD II™ CCD	AGC.....	High / Low / Off
Resolution.....	650 TV lines	White Balance	ATW / Outdoor / Indoor / Manual / AWC (1,700°K - 11,000°K)
Minimum Illumination.....	CDS Off: 0.15 lux CDS On: 0.00002 lux	Intensifier3®	Auto / Off (selectable x2 - x512)
Effective Pixels	768 (H) x 494 (V)	Motion Detection.....	On / Off (8 programmable zones)
Total Pixels	811 (H) x 508 (V)	Privacy Masking	On / Off (12 programmable zones)
TV System.....	NTSC, PAL	Speco DNR.....	On / Off (level adjustable)
Scanning Frequency.....	15.734kHz (H) & 59.94Hz (V)	Digital Zoom	On / Off (1x - 16x)
Scanning System.....	2:1 interlace	DIS.....	On / Off
Synchronization	Internal	Sharpness	On / Off (level adjustable)
S/N Ratio	More than 52dB	Flip / Mirror	On / Off
Video Output.....	CVBS: 1.0Vp-p / 75 ohms	Power Supply	12VDC / 24VAC dual voltage operation (power supply not included)
Electronic Shutter Speed.....	1/60 sec. - 1/120,000 sec.	Power Consumption	12VDC, 380mA / 24VAC, 170mA
OSD.....	Available	Operating Temperature.....	-4° F – 140° F
WDR.....	On / Off (level adjustable)	Dimensions.....	3.46" (H) x 5.1" (Dia.)
Backlight Compensation.....	BLC / HLC / Off	Weight	1 lb.
Day/Night.....	Color / BW / Auto		

Optional Accessories



INTPM
Pendant
Mount



CVCJBD
Dome Camera
Junction Box



INTWM
Wall Mount



DFM
Tile Ceiling Flush
Mount Accessory



PSW4
24VAC
Power Supply



PSW5
12VDC
Power Supply



*Chameleon Cover™ - for best results when used outdoors, waterproof paint is recommended. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Rev. 6/28/13