


Full HD 1080p 2MP Indoor Miniature Dome IP Camera

O2DP9 3.7mm fixed lens, white housing

Features

- Supports up to Full HD 1080p @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- Built-in IR LEDs
- IR Range: 30' (depending on scene reflection)
- Wide dynamic range (WDR) operation
- Supports H.264 and MJPEG codecs
- ONVIF Profile S listed*
- 2 year warranty



Camera Specifications

Image Sensor Progressive scan 1/2.9" CMOS, 2.0MP
 Maximum Resolution 1920x1080
 Minimum Illumination F2.0, 0.2 lux (IR on – 0 lux)
 S/N Ratio 50dB
 IR LEDs 12
 IR Range 30' (depending on scene reflection)
 White Balance AWB
 Exposure Control Yes
 Digital Slow Shutter Yes
 WDR/BLC WDR
 Day/Night IR-cut filter
 DNR 2D/3D

Video Specifications

Supported Resolutions ... Main profile: 1920x1080 / 1280x720 @ 30fps
 Compression H.264 (MP/BP), MJPEG
 Bitrate Control VBR, CBR
 Multiple Streaming 3 simultaneous profiles

External Terminal Specifications

Ethernet 10/100 Mbps
 Power DC jack

Network Specifications

Protocols IPv4, TCP, UDP, RTCP, RTP, RTSP, HTTP, SMTP, FTP, DHCP, UPnP, NTP, DNS
 DDNS support Speco DDNS (free of charge)
 Security User ID & Password protection, IP address filtering, HTTPS, digest authentication, user access log
 User Access 8 simultaneous users at D1 resolution
 Number of users may vary depending on resolution

System Specifications

PoE Standard (IEEE 802.3af)
 Analytics Motion detection (3 regions)
 Events FTP video file upload, email image upload
 Video Buffer Configurable pre-record & post-record
 Image Settings Text overlay, privacy mask

Client Specifications

Web Browser Support .. Windows
 (Internet Explorer 8 and up, Chrome, Firefox**)
 Mobile Apps Speco OnSIP (iPhone®, iPad® and Android™)
 PC Application Speco NVR, SecureGuard™

Operating & Unit Specifications

Power Supply PoE, 12VDC (power supply not included)
 Power Consumption 7W with IR
 Operating Temperature .. 32° F – 113° F
 Operating Humidity 8% – 80% RH
 Unit dimensions 4.8" (Dia.) x 2.17" (H)
 Unit Weight 12.80 oz.
 Certifications FCC, RoHS
 Included in Package Unit, CD (manual, software), mounting screws

Free Apps with support for view on most smart devices

*Visit www.specotech.com/onvif.html for latest ONVIF support
 **Chrome and Firefox use Java which requires an initial internet connection.
 iPhone and iPad are trademarks of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 6/05/14



Optional Accessories



IPPOEINJ1295
12.95W
PoE Injector



PSW5
12VDC
Power Supply