

Intensifier3® Series Indoor/Outdoor Dome/Turret IP Camera

See Color In Almost Complete Darkness Without IR LEDs

OINT03D1G 2.8-12mm auto iris varifocal lens, dark grey housing

Features

- Amplify existing light with no distance limitations
- No problems caused by objects that reflect or absorb IR light sources
- Minimum illumination 0.00002 lux (Intensifier3® @ 512x)
- External controls for zoom and focus
- Supports up to D1 resolution @ 30fps
- Supports H.264 and MJPEG codecs
- 2-way audio communication
- IP67 compliant
- ONVIF Profile S listed*
- 2 year warranty



Camera Specifications

Image Sensor.....1/3" Sony Super HAD II™ CCD
Maximum Resolution704x480
Minimum IlluminationCDS off: 0.15 lux, CDS on: 0.00002 lux
White BalanceATW / Indoor / Outdoor / Manual
Exposure ControlYes
Digital Slow Shutter.....Yes
WDR/BLC.....BLC
Day/NightYes
DNR.....On / Off
Intensifier3®Auto / Off (selectable 2x – 512x)

Video Specifications

Supported Resolutions...704x480 / 640x480 / 704x240 / 352x240 / 176x112 @ 30fps

Compression.....H.264, MJPEG
Bitrate ControlVBR, CBR
Multiple Streaming5 simultaneous profiles

Audio Specifications

Mono Input.....64Kbps G.711
Mono Output64Kbps G.711

External Terminal Specifications

Ethernet.....10/100 Mbps
Alarm.....1 sensor input, 1 relay output
VideoAnalog test output
Audio1 mic in, 1 line out (3.5mm)
PowerDC jack

Network Specifications

ProtocolsIPv4, IPv6, TCP, UDP, RTCP, RTP, RTSP, HTTP, HTTPS, SMTP, FTP, DHCP, UPnP, NTP, DNS

Network Specifications (continued)

DDNS support.....Speco DDNS (free of charge)
SecurityUser ID & Password protection, IP address filtering, HTTPS, digest authentication, user access log
User Access8 simultaneous users at D1 resolution
Number of users may vary depending on resolution

System Specifications

PoE.....N/A
Analytics.....Motion detection (3 regions), audio detection
Alarm Triggers.....Analytics & sensor input
Alarm Events.....FTP video file upload, email image upload, alarm out
Video Buffer.....Configurable pre-record & post-record
Image SettingsText overlay, privacy mask

Client Specifications

Web Browser Support....Windows (Internet Explorer 8 and up)
Mobile Apps.....Speco ONSIP (iPhone®, iPad® and Android™)
PC Application.....Speco NVR, SecureGuard®

Operating & Unit Specifications

Power Supply12VDC (power supply not included)
Power Consumption.....6W
Operating Temperature ...-13° F – 122° F
Operating Humidity8% – 80% RH
Unit Dimensions.....4.37" (H) x 5.5" (Dia.)
Unit Weight.....3.1 lbs.
CertificationsFCC, RoHS
Included in Package.....Unit, CD (manual, software), mounting screws, L wrench, test monitor cable

Free Apps with support for view on most smart devices

*Visit www.specotech.com/onvif.html for latest ONVIF support
iPhone and iPad are trademarks of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/21/14



Optional Accessories

