

30 Watt RMS Public Address Amplifier

PBM30 30W P.A. amplifier

Features

Speco Technologies' UL listed Contractor Series amplifiers are designed for long-running, every day use. They can stand on their own to run a smaller installation, or be incorporated into a much larger job. With RMS power ranging from 30W to 120W, microphone and source-mixing ability, telephone paging interface and music-on-hold capability, there's practically no job where one of these amplifiers wouldn't be a perfect fit!



rear of unit

Specifications

RMS Output Power.....	30W
Max. Output Power.....	45W
AC Power Consumption.....	500W
Power Supply	AC 120V, 50/60Hz
Zones.....	1
Speaker Outputs.....	4/8/16 Ohms, 70/25V
Inputs.....	2 x Mic (Terminal) 1 x Aux (Stereo RCA)
Frequency Response	70Hz ~ 18KHz (±3dB)
Tone Control	50Hz ~ 15KHz (±3dB)
THD	Less than 1% @1KHz
Signal/Noise Ratio	Microphone: >55dB TEL: >60dB Line: >70 dB
Controls	Volume for each source, Tone, TEL Input Level
Telephone	TEL in and MoH Out
Indicators	Power
Dimensions.....	10.75" (W) x 3.5" (H) x 9.5" (D)
Weight	11.4 lbs.
Listings	UL, cUL, CE, FCC

Optional Accessory



PBMRK2
Rack Mounting Kit

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 7/17/14