


## Full HD 1080p 2MP Indoor Dome IP Camera

**VIP2D1M** 3-9mm auto iris varifocal motorized lens, white housing

### Features

- Supports up to Full HD 1080p @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- Motorized lens for remote focusing
- Supports H.264, MPEG4, and MJPEG codecs
- Micro SD card slot (card not included)
- ONVIF Profile S listed\*
- 2 year warranty



### Camera Specifications

Image Sensor ..... Progressive scan 1/2.7" CMOS, 2.0MP  
 Maximum Resolution .... 1920x1080  
 Minimum Illumination.... F1.2, Color: 0.9 lux; BW: 0.2 lux  
 White Balance ..... Automatic, Incandescent, Fluorescent, Outdoor  
 Exposure Control..... Yes  
 Digital Slow Shutter ..... Yes  
 WDR/BLC ..... BLC  
 Day/Night..... IR cut filter  
 DNR..... 2D

### Video Specifications

Supported Resolutions ... 1920x1080 / 1280x1024 / 1280x720 / 704x576 / 704x480 / 640x480 / 352x288 / 352x240 / 320x240 @ 30fps  
 Compression ..... H.264 (HP/MP/BP), MPEG4 (SP), MJPEG  
 Bitrate Control..... VBR, CBR  
 Multiple Streaming..... 3 simultaneous profiles

### Audio Specifications

Mono Input..... N/A  
 Mono Output..... N/A

### External Terminal Specifications

Ethernet..... 10/100 Mbps  
 Alarm ..... 1 sensor input, 1 output  
 Video ..... 3.5mm jack (test monitor)  
 Audio ..... N/A  
 Power ..... 2-pin terminal block  
 Storage..... Micro SD slot

### Network Specifications

Protocols..... IPv4, IPv6, TCP, UDP, ARP, RTCP, RTP, RTSP, HTTP, HTTPS, SMTP, FTP, DHCP, UPnP, QoS, Zeroconf, Bonjour

### Free Apps with support for view on most smart devices

\*visit [www.specotech.com/onvif.html](http://www.specotech.com/onvif.html) for latest ONVIF support. iPhone and iPad are trademarks of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/17/14



### Network Specifications (continued)

DDNS support ..... Speco DDNS (free of charge)  
 Security..... User ID & Password protection, IP address filtering, HTTPS  
 User Access..... 10 simultaneous users  
 Performance may vary depending on resolution and number of connections

### System Specifications

PoE..... Standard (IEEE 802.3af)  
 Analytics ..... Motion detection (8 regions)  
 Alarm Triggers ..... Motion, sensor input, on boot, network loss, manual  
 Alarm Events ..... FTP video file upload, email image upload, micro SD card recording, HTTP server, alarm out, boost  
 Video Buffer ..... Configurable pre-record & post-record  
 Image Settings..... Privacy mask

### Client Specifications

Web Browser Support ... Windows (Internet Explorer 8 and up, Chrome, Firefox)  
 Mobile Apps ..... Speco VIP (iPhone®, iPad® and Android™)  
 PC Application ..... Speco VMS, SecureGuard®

### Operating & Unit Specifications

Power Supply ..... PoE, 12VDC (power supply not included)  
 Power Consumption ..... PoE, 80mA / 12VDC, 340mA  
 Operating Temperature ... 14° F – 113° F  
 Operating Humidity..... 0% – 90% RH  
 Unit Dimensions ..... 4.1" (H) x 4.68" (Dia.)  
 Unit Weight..... 10 oz.  
 Certifications..... FCC, RoHS  
 Included in Package ..... Unit, CD (manual, software), mounting template sheet, mounting screws

### Optional Accessories



**IPPOEINJ1295**  
12.95W  
PoE Injector



**PSW5**  
12VDC  
Power Supply



**VIPRC**  
Remote Control