

Full HD 1080p 2MP Indoor/Outdoor Vandal Dome IP Camera

VIP2D2 3-9mm auto iris varifocal lens, white housing

Features

- Supports up to Full HD 1080p @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- Supports H.264, MPEG4, and MJPEG codecs
- 2-way audio communication
- Digital Deterrent®
- Micro SD card slot (card not included)
- IP66 and IK10 compliant
- ONVIF Profile S listed*
- 2 year warranty



Camera Specifications

Image Sensor.....	Progressive scan 1/2.8" Sony Exmor CMOS, 2.0MP
Maximum Resolution	1920x1080
Minimum Illumination	F1.2, Color: 0.2 lux, BW: 0.01 lux
IR LEDs.....	N/A
IR Range	N/A
White Balance	Automatic, Manual
Exposure Control	Yes
Digital Slow Shutter.....	Yes
WDR/BLC.....	BLC
Day/Night	IR cut filter
DNR.....	2D

Video Specifications

Supported Resolutions...	1920x1080 / 1280x1024 / 1280x720 / 704x576 / 704x480 / 640x480 / 320x240 @ 30fps
Compression	H.264 (HP/MP/BP), MPEG4 (SP), MJPEG
Bitrate Control	VBR, CBR
Multiple Streaming	3 simultaneous profiles

Audio Specifications

Mono Input	64Kbps G.711
Mono Output	64Kbps G.711

External Terminal Specifications

Ethernet.....	10/100 Mbps
Alarm	1 sensor input, 1 output
Video	3.5mm jack (test monitor)
Audio	3.5mm jack
Power	2-pin terminal block
Storage.....	Micro SD slot

Network Specifications

Protocols	IPv4, IPv6, TCP, UDP, RTCP, RTP, RTSP, HTTP, HTTPS, SMTP, FTP, DHCP, Bonjour
DDNS support.....	Speco DDNS (free of charge)
Security	User ID & Password protection, IP address filtering, HTTPS
User Access	10 simultaneous users. Performance may vary depending on resolution and number of connections

System Specifications

PoE.....	Standard (IEEE 802.3af)
Analytics	Motion detection (8 regions)
Alarm Triggers.....	Motion, sensor input, on boot, network loss, manual
Alarm Events.....	FTP video file upload, email image upload, micro SD card recording, HTTP server, alarm out, boost
Video Buffer.....	Configurable pre-record & post-record
Image Settings	Privacy mask

Client Specifications

Web Browser Support....	Windows (Internet Explorer 8 and up, Chrome, Firefox)
Mobile Apps.....	Speco VIP (iPhone®, iPad® and Android™)
PC Application.....	Speco VMS, SecureGuard®


Operating & Unit Specifications

Power Supply	PoE, 12VDC, 24VAC (power supply not included)
Power Consumption.....	6W
Operating Temperature ..	-4° F – 122° F
Operating Humidity	0% – 90% RH
Unit Dimensions	4.74" (H) x 5.98" (Dia.)
Unit Weight.....	2.56 lbs.
Certifications	FCC, RoHS
Included in Package.....	Unit, CD (manual, software), mounting template sheet, mounting screws, alarm cable

Optional Accessories



APT32DW
Adaptor Plate



COR32DW
Corner Mount
Adaptor, use
with APT32DW



IPPOEINJ1295
12.95W
PoE Injector



POL28DW
Pole Mount
use with
APT32DW



WMA29DW
Wall Mount



VIPRC
Remote
Control



WAC29DW
Wall/ Ceiling
Adaptor



PSW4
24VAC
Power Supply



PSW5
12VDC
Power Supply

Free Apps with support for view on most smart devices

*Visit www.specotech.com/onvif.html for latest ONVIF support. iPhone and iPad are trademarks of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/17/14

