


## Full HD 1080p 2MP Indoor/Outdoor Vandal Resistant Dome IP Camera

**VIP2D2M** 3-9mm auto iris varifocal motorized lens, white housing



### Features

- Supports up to Full HD 1080p @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- Built-in IR LEDs
- IR Range: 65' (depending on scene reflection)
- Motorized lens for remote focusing
- Supports H.264, MPEG4, and MJPEG codecs
- 2-way audio communication
- Digital Deterrent®
- Micro SD card slot (card not included)
- IP66 and IK10 compliant
- ONVIF Profile S listed\*
- 2 year warranty

### Camera Specifications

Image Sensor .....	Progressive scan 1/2.8" Sony Exmor CMOS, 2.0MP
Maximum Resolution .....	1920x1080
Minimum Illumination .....	F1.2, Color: 0.2 lux, BW: 0.01 lux
IR LEDs .....	24
IR Range .....	65' (depending on scene reflection)
Focus .....	Motorized remote focus
White Balance .....	Automatic, Manual
Exposure Control .....	Yes
Digital Slow Shutter .....	Yes
WDR/BLC .....	BLC
Day/Night .....	IR cut filter
DNR .....	2D

### Video Specifications

Supported Resolutions .....	1920x1080 / 1280x1024 / 1280x720 / 704x576 / 704x480 / 640x480 / 320x240 @ 30fps
Compression .....	H.264 (HP/MP/BP), MPEG4 (SP), MJPEG
Bitrate Control .....	VBR, CBR
Multiple Streaming .....	3 simultaneous profiles

### Audio Specifications

Mono Input .....	64Kbps G.711
Mono Output .....	64Kbps G.711

### External Terminal Specifications

Ethernet .....	10/100 Mbps
Alarm .....	1 sensor input, 1 output
Video .....	3.5mm jack (test monitor)
Audio .....	3.5mm jack
Power .....	2-pin terminal block
Storage .....	Micro SD slot

### Network Specifications

Protocols .....	IPv4, IPv6, TCP, UDP, RTCP, RTP, RTSP, HTTP, HTTPS, SMTP, FTP, DHCP, Bonjour
-----------------	--

### Network Specifications (continued)

DDNS support .....	Speco DDNS (free of charge)
Security .....	User ID & Password protection, IP address filtering, HTTPS
User Access .....	10 simultaneous users
	Performance may vary depending on resolution and number of connections

### System Specifications

PoE .....	Standard (IEEE 802.3af)
Analytics .....	Motion detection (8 regions)
Alarm Triggers .....	Motion, sensor input, on boot, network loss, manual
Alarm Events .....	FTP video file upload, email image upload, micro SD card recording, HTTP server, alarm out, boost
Video Buffer .....	Configurable pre-record & post-record
Image Settings .....	Privacy mask

### Client Specifications

Web Browser Support .....	Windows (Internet Explorer 8 and up, Chrome, Firefox)
---------------------------	---

Mobile Apps .....

PC Application .....

### Operating & Unit Specifications

Power Supply .....	PoE, 12VDC, 24VAC (power supply not included)
Power Consumption .....	8W with IR
Operating Temperature .....	-4° F – 122° F
Operating Humidity .....	0% – 90% RH
Unit Dimensions .....	4.74" (H) x 5.98" (Dia.)
Unit Weight .....	2.56 lbs.
Certifications .....	FCC, RoHS
Included in Package .....	Unit, CD (manual, software), mounting template sheet, mounting screws, alarm cable

### Optional Accessories



**APT32DW**  
Adaptor Plate



**COR32DW**  
Corner Mount Adaptor, use with APT32DW



**IPPOEINJ1295**  
12.95W PoE Injector



**POL28DW**  
Pole Mount use with APT32DW



**VIPRC**  
Remote Control



**WMA29DW**  
Wall Mount



**WAC29DW**  
Wall/ Ceiling Adaptor



**PSW4**  
24VAC Power Supply



**PSW5**  
12VDC Power Supply

### Free Apps with support for view on most smart devices

\*Visit [www.specotech.com/onvif.html](http://www.specotech.com/onvif.html) for latest ONVIF support. iPhone and iPad are trademarks of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/18/14

