

INSTALLATION MANUAL

ENFORCER®

SS-077 and SS-078

Hold-up Buttons

- Highly reliable switch mechanism
- Attractive, durable stainless steel housing
- Compact size
- High-security key reset
- Use with either N.C. or N.O. inputs



The SS-077 and SS-078 Hold-up Buttons are the perfect units for activating hold-up circuits, cameras, etc. Because of its superior construction and solid-state design, these units can be used for silent operation, or, if you wish, these units can be conveniently connected to sound a bell, siren, or other signalling device when triggered. The highly reliable switch mechanism ensures that these units will give you years and years of trouble-free operation.

Once activated, the SS-077 and SS-078 latch-in and an indicator flag will clearly show which hold-up switch was depressed - a great help when more than one unit is used. The unit can only be reset by authorized person with the key.

Contacts	
SS-077-	Normally closed, latching open
SS-077-	Normally open, latching closed
Switch Type	SPST
Switch rating	12VDC @ 1Amp
Terminal type	Screws (2)
Mounting type	Surface
Size	
(L) -	2-3/4" (70mm)
(W) -	1-1/4" (56mm)
(H) -	1-1/16" (27mm)
Case	ABS plastic
Cover	Stainless steel

SS-077



Red Push Button

N.C.

Red Push Button

With SS-077 the magnet is in the **UP (N.C.)** position.

SS-078



N.O.

With SS-078 the magnet is in the **DOWN (N.O.)** position.

SLI®

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Tel: 800-662-0800 / 949-261-2999 Fax: 949-261-7326

FILE: mi-SS-077_78.pmd/MAR2006