

# STI Wireless Receivers

*Home &  
Work Series*




STI-34104



STI-34108



STI-34098



STI-34188



STI-V34104

## PRODUCT OVERVIEW

The receivers allow you to monitor up to 8 different STI wireless alert devices at a single, convenient location. Supervised for low battery and signal reception, they have an audible chime tone or 12 VDC output for siren. The 4-Channel Voice Receiver sounds a tune or a prerecorded programmable voice message. Offers ten tones/tunes or 53 selectable words (English or Spanish) to create a custom message up to four words. The 8-Channel Receiver offers a mirror function that can work with up to four additional 8-Channel Receivers. Devices can be latching or momentary by zone. STI offers multiple wireless products designed to alert you of several different conditions (such as: an open garage door, mail delivered, a car in the driveway, open exit door, removed fire extinguisher or activated push button, etc.).

## HOW IT WORKS

The receivers (excludes Single Channel Slave) supervise transmitter battery and signal reception (low battery is indicated with a short beep between 12 and 24 hours of detection).

## FEATURES

- Monitor 4 or 8 devices at a single, convenient location.
- Supervised for low battery and signal reception.
- Operates up to 1000' (line of sight), 433MHz.
- Audible chime tone and 12 volt output.
- Devices can be latching or momentary by each zone. (STI-V34104 & STI-34108)
- Includes 12 volt power supply.
- **STI-34104**
  - \* Monitors up to 4 devices.
  - \* Distinct beep and tone for each of the four devices.
  - \* Latching memory LED (flashes until reset).
  - \* Input power is 12 volt, 75mA.
- **STI-V34104**
  - \* Monitors up to 4 devices.
  - \* Ten tones/tunes or 53 selectable words (English or Spanish).
  - \* Words can be programmed in sets of up to four to create custom message.
- **STI-34108**
  - \* Monitors up to 8 devices with 8 zone LED indicators.
  - \* Mirror function (works with up to 4 additional 8-Channel Receivers).
  - \* Dual antennas for increased signal strength.
  - \* Form "C" contact for remote monitoring.
  - \* 300mA, 12 volt available for siren output (with 500mA, 12 volt supply).
  - \* Measures 5 ¼ x 5 ¾ x 1 ¼".
  - \* Key fob available for alert or on/off.
- **STI-34098**
  - \* Allows transmitters to connect to control panel.
- **STI-34188**
  - \* 8-Zone Relay Board for STI-34108.
  - \* 8 momentary Form "C" relay contacts rated 3A, 125 VAC, 3A 28VDC.

# STI Wireless Receivers

Dimensions and Technical Information

## MODELS AVAILABLE

### Receivers

STI-34104	4-Channel Receiver
STI-34108	8-Channel Receiver
STI-V34104	4-Channel Voice Receiver
STI-34098	Single Channel Slave Receiver

### Sensors

STI-34101	Wireless Driveway Monitor Sensor (solar powered)
STI-34151	Wireless Driveway Monitor Sensor (battery powered)
STI-34201	Wireless Mailbox Alert Sensor
STI-34301	Wireless Garage Sentry Alert Sensor
STI-34401	Wireless Universal Alert Sensor
STI-34451	Wireless Door Chime Sensor
STI-34601	Wireless Doorbell Button Alert Sensor
STI-34701	Wireless Indoor Motion Detector Alert Sensor
STI-34751	Wireless Outdoor Motion Detector Alert Sensor
STI-6200WIR	Wireless Fire Extinguisher Theft Stopper® Sensor
STI-6400WIR	Wireless Exit Stopper® Door Alarm Sensor
STI-6517B	Wireless Stopper® Station Shield with Sound and Wireless Transmitter

### 4-Channel Receiver Kits

STI-34100	Wireless Driveway Monitor (solar powered)
STI-34150	Wireless Driveway Monitor (battery powered)
STI-34200	Wireless Mailbox Alert
STI-34300	Wireless Garage Sentry Alert
STI-34400	Wireless Universal Alert
STI-34450	Wireless Door Chime
STI-34600	Wireless Doorbell Button Alert
STI-34700	Wireless Indoor Motion Detector Alert
STI-34750	Wireless Outdoor Motion Detector Alert

### Single Channel Slave Receiver Kits

STI-34119	Wireless Driveway Monitor (solar powered)
STI-34159	Wireless Driveway Monitor (battery powered)
STI-34209	Wireless Mailbox Alert
STI-34309	Wireless Garage Sentry® Alert
STI-34409	Wireless Universal Alert
STI-34609	Wireless Doorbell Button Alert
STI-34709	Wireless Indoor Motion Detector Alert
STI-34759	Wireless Outdoor Motion Detector Alert

## APPROVALS

### TESTING

- STI-34104, STI-34108, STI-V34104
- CE
  - FCC & IC Compliant

### 4-Channel Voice Receiver Kits

STI-V34100	Wireless Driveway Monitor (solar powered)
STI-V34150	Wireless Driveway Monitor (battery powered)
STI-V34200	Wireless Mailbox Alert
STI-V34300	Wireless Garage Sentry Alert
STI-V34400	Wireless Universal Alert
STI-V34450	Wireless Door Chime
STI-V34600	Wireless Doorbell Button Alert
STI-V34700	Wireless Indoor Motion Detector Alert
STI-V34750	Wireless Outdoor Motion Detector Alert

### Accessories

STI-34099	Single Channel Slave Receiver Case
STI-34105	Voltamax 12 VDC (500mA) power supply
STI-30104	Lamp Controller
STI-30105	Extended antenna
STI-34106	Key Fob
STI-34109	Repeater - Extends Transmitter range up to 1000'
STI-34188	8-Zone Relay Board for STI-34108



**Safety Technology  
International, Inc.**

2306 Airport Road  
Waterford, Michigan  
48327, USA

Tel: 248-673-9898  
Fax: 248-673-1246  
Toll-free: 800-888-4784  
info@sti-usa.com  
www.sti-usa.com

Unit 49G Pipers Road  
Park Farm Industrial Estate  
Redditch, Worcestershire  
B98 0HU England

Tel: 44 (0) 1527 520 999  
Fax: 44 (0) 1527 501 999  
Free: 0800 085 1678 (UK)  
www.sti-europe.com