

Safety Technology International, Inc.

2306 Airport Road • Waterford, Michigan 48327-1209 Phone: 248-673-9898 • Fax: 248-673-1246 Toll Free: 800-888-4784 • E-mail: info@sti-usa.com

Web: www.sti-usa.com

Safety Technology International (Europe) Ltd.
Unit 49G Pipers Road • Park Farm Industrial Estate • Redditch
Worcestershire • B98 OHU • England
Tel: 44 (0) 1527 520 999 • Fax: 44 (0) 1527 501 999
E-mail: info@sti-europe.com • Web: www.sti-europe.com

**GASKET MAY BE SLIT IN** THIS AREA AND PLACED #70495 CONDUIT ENTRY GASKET BEHIND CONDUIT SELECT THE PROPER DIAMETER, PUSH OUT AND DISCARD INSTALLATION INSTRUCTIONS 1. The (6) mounting holes must be marked and drilled with the (6) anchors installed prior to the installation of the #70496 gasket. 2. After the #70496 gasket is installed the #70495 gasket (if needed) may now be placed around conduit. 3. Place #70498 gasket into the groove on the bottom side of cover and complete installation as shown. #70496 GASKET PEEL OFF BACKING PAPER AND PLACE ADHESIVE SIDE TOWARD WALL #19049 WASHER (6) PROVIDED #70498 GASKET -#19050 #8-32 x 3/4 in. SOCKET HEAD SCREW

Electronic warranty form at www.sti-usa.com/wc14

## **INSTALLATION OF SUB-123 ENVIRO-KIT**

All specifications and information shown were current as of publication and are subject to change without notice.

