

Staggered "T" Contacts

TERMINAL CONTACTS

Introducing Honeywell's exclusive Staggered "T" Terminal Contacts. The staggered design means larger screw terminals and easier wiring.

The larger terminal idea was introduced with our popular PAL-T surface contact and is now available on the new Staggered "T" recessed contacts. Choose from the 944T (3/8" diameter), 944TSP (with 3/4" switch and 3/8"

magnet), or the 947-75T for steel doors. Our unique mini-plunger contacts (955PST/956RPT) have been lab tested in over 18,000,000 actual activations without a single failure. Exclusive Staggered "T" terminals eliminate splice, solder and tape and are compatible with standard size screwdrivers.

955PST Mini Plunger Switch with Terminals

- Broad face plunger distributes impact more evenly
- Also available with leads (955PS)



956RPT Mini Roller Plunger Switch with Terminals

- Shorter body for easier recess fit
- Also available with leads (956RP)
- Full 180° activation



944T 3/8" Recessed Contact with Screw Terminals

- 3/8" diameter press fit design
- Standard gap: 3/4"



944TSP 3/4" Recessed Contact with Terminals and 3/8" Magnet

- 3/4" diameter switch for easier wiring; supplied with 3/8" diameter magnet
- Standard gap: 3/4"



947-75T 3/4" Recessed Steel Door Contact with Screw Terminals

- 3/4" diameter recessed contact for steel doors
- Standard gap: 1/2" in steel



Staggered "T" Contacts

TERMINAL CONTACTS

SPECIFICATIONS

- **Contact Type**

Recessed magnetic reed contact

- **Switch Type**

Form A (SPST) reed switch/closed when energized with actuator magnet

Plunger switches closed with actuator depressed

- **Switch Rating**

24 VDC at 100mA continuous

- **Gap**

944T: 3/4" (19mm)

944TSP: 3/4" (19mm)

947-75T: 1-1/4" (32mm) standard, 1/2" (13mm) in steel

- **Wiring**

Screw terminals for wire gauge of 24 to 18AWG. Solid or stranded wire.

- **Dimensions**

955PST: 3/4" (19mm) diameter x 1.20" (30mm) L

955PS: 3/4" (19mm) diameter x .50" (12mm) L

956RPT: 3/4" (19mm) diameter x 1.20" (30mm) L

956RP: 3/4" (19mm) diameter x .50" (12mm) L

944T: Switch – 3/4" (19mm) diameter x 1.37" (35mm) L

Magnet – 3/4" (19mm) diameter x 1.30" (33mm) L

947-75T: Switch – 3/4" (19mm) diameter x 1.37" (35mm) L

Magnet – 3/4" (19mm) diameter x 1.66" (42mm) L

- **Agency Listings**

- UL, ULC, CE



955PST with unique broad face actuator, distributes impact more evenly



944T recessed contact with staggered terminals

ORDERING

955PST	Mini Plunger Switch
955PS	Mini Plunger Switch with Wire Leads
956RPT	Mini Roller Plunger Switch
956RP	Mini Roller Plunger Switch with Wire Leads
944T 3/8"	Diameter Recessed Contact
944TSP 3/4"	Recessed Contact with 3/8" Magnet
947-75T 3/4"	Diameter Recessed Steel Door Contact
Specify Color:	WH (white), BR (brown) or GY (gray)

Automation and Control Solutions

Honeywell Security & Communications
2 Corporate Center Dr. Suite 100
P.O. Box 9040
Melville, NY 11747
www.honeywell.com

Honeywell

L/STGT/D
September 2008
© 2008 Honeywell International Inc.